2291931-1 🗸 ACTIVE

CDFP

TE Internal #: 2291931-1 CDFP, Cage Assembly with Integrated Connector, 1 Port, Data Rate (Max) 400 Gb/s, Elastomeric Gasket, Cable-to-Board, 60 Position, CDFP

View on TE.com >

Connectors > Pluggable IO Connectors & Cages > CDFP > CDFP Cage Assemblies



Pluggable I/O Product Type: Cage Assembly with Integrated Connector

Number of Ports: 1

Data Rate (Max): 400 Gb/s

EMI Containment Feature Type: Elastomeric Gasket

Connector System: Cable-to-Board

All CDFP Cage Assemblies (3)



Features

Prod	luct ⁻	Гуре	Featu	res
		· / · · ·		

Form Factor	CDFP Style 1			
Cage Туре	Single			
Pluggable I/O Product Type	Cage Assembly with Integrated Connector			
Connector System	Cable-to-Board			
Sealable	Yes			
Connector & Contact Terminates To	Printed Circuit Board			
Configuration Features				
Port Configuration	Single Port			
Number of Ports	1			
Number of Positions	60			
Electrical Characteristics				
Data Rate (Max)	400 Gb/s			

CDFP, Cage Assembly with Integrated Connector, 1 Port, Data Rate (Max) 400 Gb/s, Elastomeric Gasket, Cable-to-Board, 60 Position, CDFP



Body Features

Cage Plating Material	Nickel			
Contact Features				
Contact Base Material	Phosphor Bronze			
Termination Features				
Termination Method to Printed Circuit Board	Through Hole - Press-Fit			
Mechanical Attachment				
PCB Mounting Style	Single-Sided			
Connector Mounting Type	Board Mount			
Housing Features				
Cage Material	Zinc Alloy			
Centerline (Pitch)	.75 mm[.03 in]			
Dimensions				
Product Length	54.3 mm[2.139 in]			
Usage Conditions				
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]			

Operation/Application

Circuit Application	Signal
Other	
EMI Containment Feature Type	Elastomeric Gasket
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

CDFP, Cage Assembly with Integrated Connector, 1 Port, Data Rate (Max) 400 Gb/s, Elastomeric Gasket, Cable-to-Board, 60 Position, CDFP



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






Also in the Series | CDFP



Customers Also Bought

CDFP, Cage Assembly with Integrated Connector, 1 Port, Data Rate (Max) 400 Gb/s, Elastomeric Gasket, Cable-to-Board, 60 Position, CDFP





Documents

Product Drawings CDFP RCPT CONNECTOR & CAGE STYLE 1

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2291931-1_B.2d_dxf.zip

English

Customer View Model ENG_CVM_CVM_2291931-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2291931-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

C For support call+1 800 522 6752

CDFP, Cage Assembly with Integrated Connector, 1 Port, Data Rate (Max) 400 Gb/s, Elastomeric Gasket, Cable-to-Board, 60 Position, CDFP



CDFP Connector and Cage Assembly CN

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Instruction Sheets

Instruction Sheet (U.S.)

English