

# XP263N1001TR-G

N-channel MOSFET 60V, 1A

ETR11048-001


## FEATURES

On-State Resistance :  $R_{DS(on)}=0.25\Omega @V_{GS}=10V$   
 Driving voltage : 4.5V  
 Environmentally Friendly : EU RoHS Compliant, Pb Free

## APPLICATIONS


● Switching

## EQUIVALENT CIRCUIT



## PIN CONFIGURATION

● SOT-23(TO-236)



## PRODUCT NAME

PRODUCT NAME	PACKAGE	ORDER UNIT
XP263N1001TR-G *	SOT-23(TO-236)	3,000 pcs/ Reel

\* The "-G" suffix denotes Halogen and Antimony free as well as being fully EU RoHS compliant

## ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	$V_{DSS}$	60	V
Gate-Source Voltage	$V_{GSS}$	$\pm 20$	V
Drain Current (DC)	$I_D$	1	A
Drain Current(Pulse) <sup>(1)</sup>	$I_{DP}$	2	A
Channel Power Dissipation <sup>(2)</sup>	$P_d$	0.4	W
Junction Temperature	$T_J$	150	$^{\circ}C$
Storage Temperature	$T_{stg}$	-55~150	$^{\circ}C$

<sup>(1)</sup> $PW \leq 10\mu s$ , duty cycle  $\leq 1\%$

<sup>(2)</sup>When implemented on a PCB defined by JESD51-7

## ELECTRICAL CHARACTERISTICS

Ta=25°C


PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D = 250\mu A, V_{GS} = 0V$	60	-	-	V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS} = 60V, V_{GS} = 0V$	-	-	1	$\mu A$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS} = \pm 20V, V_{DS} = 0V$	-	-	$\pm 10$	$\mu A$
Gate Threshold Voltage	$V_{GS(off)}$	$I_D = 250\mu A, V_{DS} = V_{GS}$	1.1	1.7	2.4	V
Drain-Source On Resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 500mA$	-	0.18	0.25	$\Omega$
		$V_{GS} = 4.5V, I_D = 500mA$	-	0.23	0.33	$\Omega$
Input Capacitance	$C_{iss}$	$V_{DS} = 20V, V_{GS} = 0V$ $f = 1MHz$	-	180	-	pF
Output Capacitance	$C_{oss}$		-	32	-	pF
Reverse Transfer Capacitance	$C_{rss}$		-	22	-	pF
Turn-on Delay Time	$t_{d(on)}$	$V_{DD} = 10V, I_D = 500mA$ $V_{GS} = 10V$	-	10	-	ns
Rise Time	$t_r$		-	8	-	ns
Turn-off Delay Time	$t_{d(off)}$		-	35	-	ns
Fall Time	$t_f$		-	10	-	ns
Total Gate Charge	$Q_g$		$V_{DS} = 20V, I_D = 500mA$ $V_{GS} = 10V$	-	3.6	-
Gate-Source Charge	$Q_{gs}$	-		0.6	-	nC
Gate-Drain Charge	$Q_{gd}$	-		0.8	-	nC
Diode Forward Voltage	$V_{SD}$	$I_S = 500mA, V_{GS} = 0V$	-	0.7	1	V

## NOTES ON USE


- Please use this IC within the absolute maximum ratings.  
Even within the ratings, in case of high load use continuously such as high temperature, high voltage, high current and thermal stress may cause reliability degradation of the IC.
- Torex places an importance on improving our products and their reliability.  
We request that users incorporate fail-safe designs and post-aging protection treatment when using Torex products in their systems.

# TYPICAL PERFORMANCE CHARACTERISTICS


(1) Drain Current vs. Drain-Source Voltage




(2) Drain Current vs. Gate-Source Voltage




(3) Drain-Source On Resistance vs. Gate-Source Voltage




(4) Drain-Source On Resistance vs. Ambient Temperature



(5) Drain-Source On Resistance vs. Drain Current




(6) Source Current vs. Diode Forward Voltage




## TYPICAL PERFORMANCE CHARACTERISTICS


(7) Ciss, Coss, Crss vs. Drain-Source Voltage



(8) Gate-Source Voltage vs. Gate Charge



(9) Area of Safe Operation



## ■ PACKAGING INFORMATION

For the latest package information go to, [www.torexsemi.com/technical-support/packages](http://www.torexsemi.com/technical-support/packages)

PACKAGE	OUTLINE / LAND PATTERN	THERMAL CHARACTERISTICS	
SOT-23(TO-236)	<a href="#">SOT-23(TO-236) PKG</a>	JESD51-7 Board	<a href="#">SOT-23(TO-236) PowerDissipation</a>

## ■ MARKING RULE

### ● SOT-23(TO-236)

① ② ③ represents product series


MARK			PRODUCT SERIES
①	②	③	
6	3	N	XP263N1001**-G

④, ⑤ represents production lot number

01 to 09, 0A to 0Z, 11 to 9Z, A1 to A9, AA to AZ, B1 to ZZ repeated  
(G, I, J, O, Q, W excluded)

\*No character inversion used

SOT-23(TO-236)



1. The product and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date.
2. The information in this datasheet is intended to illustrate the operation and characteristics of our products. We neither make warranties or representations with respect to the accuracy or completeness of the information contained in this datasheet nor grant any license to any intellectual property rights of ours or any third party concerning with the information in this datasheet.
3. Applicable export control laws and regulations should be complied and the procedures required by such laws and regulations should also be followed, when the product or any information contained in this datasheet is exported.
4. The product is neither intended nor warranted for use in equipment of systems which require extremely high levels of quality and/or reliability and/or a malfunction or failure which may cause loss of human life, bodily injury, serious property damage including but not limited to devices or equipment used in 1) nuclear facilities, 2) aerospace industry, 3) medical facilities, 4) automobile industry and other transportation industry and 5) safety devices and safety equipment to control combustions and explosions. Do not use the product for the above use unless agreed by us in writing in advance.
5. Although we make continuous efforts to improve the quality and reliability of our products; nevertheless Semiconductors are likely to fail with a certain probability. So in order to prevent personal injury and/or property damage resulting from such failure, customers are required to incorporate adequate safety measures in their designs, such as system fail safes, redundancy and fire prevention features.
6. Our products are not designed to be Radiation-resistant.
7. Please use the product listed in this datasheet within the specified ranges.
8. We assume no responsibility for damage or loss due to abnormal use.
9. All rights reserved. No part of this datasheet may be copied or reproduced unless agreed by Torex Semiconductor Ltd in writing in advance.

TOREX SEMICONDUCTOR LTD.