



NOTES:

1. METALSHHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. NO CONTACTS ON POS. A1 - A3
5. CONNECTOR IS PART MARKED: 3025W3PAM99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH. DO NOT ALTER CAD DRAWING BY HAND

tolerance			scale: 2:1 (5:1)	
dim. in mm			material: SEE NOTES	
drawn	09.01.13	date	title: D-SUB COMBINATION MALE	
appd.	09.01.13	name	25W3P SOLDER CUP	
norm			dwg no: 13K1A4148	
d-old			DIN-A3	
a	Original			sh: 1
rev.	description	date	name	part no: 3025W3PAM99A10X