



MODULAR JACKS AND PLUGS: GDCX-P Series
Vertical Through Hole

Product Features

- Available in 4, 6, and 8 Position Housings
- Vertical Mount
- Through Hole Contacts
- CSA/NRTL Certified File No. LR78160
- UL File No. E134345

Performance Specifications

Materials and Finish

Housing Material

PBT Thermoplastic, UL 94V-0 Rated, Black Color

Contact Material

Phosphor Bronze

Electrical Characteristics

Insulation Resistance

500 Megohms Min.

Dielectric Withstanding Voltage

1000V RMS, 60Hz

Contact Resistance

20 milliohms Max.

Voltage Rating

125V DC

Current Rating

1.5A

Operating Temperature

-40°C to +85°C

Durability Rating

500 Mating Cycles Min.

Generated Part Number

GDCX-PA-44

Part Number Builder

GDCX-P	A		44		
Series	Panel Stop Option	Shield Option	Positions & Contacts	Keyed Option	Plating Option

Series

GDCX-P - Perpendicular Through Hole Modular Jacks

Panel Stops

- A - With Panel Stops
- N - Without Panel Stops

Shield Options

- Blank - Non-Shielded
- S - Shielded (Available Only with 8P8C Option)

Number of Positions / Contacts

- - 4 Postions / 4 Contacts
- - 6 Positions / 4 Contacts
- - 6 Positions / 6 Contacts
- - 8 Positions / 8 Contacts

Keyed Option

- - Not Keyed
- - Keyed (Only for 8P8C)

Plating Option

- Blank - Gold Flash
- - 50µ" Gold Plating

Contact Kycon for Other Options

GDCX-Px-88

Dimensions in mm

