

Product data sheet

Specifications



Netshelter RX 24U Enclosure 600mm x 800mm

NSYSFRSEDC12680

Overview

Presentation	NEMA 12 rated assembled enclosure for OT, IT and networking applications. Form factor to easily roll through doorways. Configurable to work as a ventilated enclosure with the addition of Climasys ventilation components. Includes: Front and rear solid doors with handle and insert key, side panels, 19" uprights, bottom plinth, grounding and gland plate at the bottom panel. Ventilation system not included. Can be shipped pre-integrated with UPS, PDU, monitoring components and internal equipment up to 350 lbs.
Lead time	Usually Ships within 4 Weeks

Physical

Height	1300 mm
Width	600 mm
Depth	800 mm
Number of rack unit	24U
Product weight	100 kg
Mounting mode	Rack-mounted
Mounting preference	No preference
Maximum mounting depth	652 mm
Max CTO ship weight	125 kg
Permanent permissible load	113 kg dynamic 400 kg static

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	148.0 cm
Package 1 Width	74.0 cm
Package 1 Length	116.0 cm
Package 1 Weight	151.00 kg

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
--------------------------	--

Recommended replacement(s)