

Mallory Sonalert Products, Inc.

Part #:

LSC110N

Sales Outline Drawing

Revision:

G

Specifications:

| | |
|-----------------------|--|
| Sound Level Category | Loud |
| Mode of Operation | Continuous - LED Blinking @ 2 ± 1.5 PPS |
| Voltage Rating | 30 to 120 VAC/DC |
| Frequency | 2900 ± 500 Hz |
| Loudness @ 2 FT | 90 to 102 dB(A) Typ. |
| Loudness @ Min Vdc | 80 dB(A) @ 2 Feet and 30 Vdc |
| Loudness @ Max Vdc | 95 dB(A) @ 2 Feet and 120 Vdc |
| Current Draw | 43-63mA |
| Duty Cycle (%) | 50 |
| Housing Material | 6/6 Nylon, Color: Black |
| Storage Temperature | -40° to +85° C |
| Operating Temperature | -30° to +65° C |
| Panel Mounting | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |
| Knurled Nut | Used to attach part to panel. The max recommended torque is 10 in-lbs. |
| Weight (Typical) | 1.6 oz (45g) |
| NEMA 3R,4X, & 12 | Approved with use of ACC03. |
| Options | Please contact factory. |

Dimensions: Inches (mm)

Before Code Date: 2018 5

After Code Date: 2019 1

