

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
E		ECR-09-007414	02JUN2009	KG	DW
F		ECR-17-001574	11APR2017	KG	DW

1. USE WITH FERRULE ASSEMBLY KIT P/N 1588908-2 (125um), OR 1588908-1 (126um). QUANTITY OF 2 REQUIRED. FERRULE MUST BE PC-POLISHED DURING FIBER TERMINATION FOR BEST PERFORMANCE.

2. PROTECTIVE LABEL APPLIED AFTER FINAL CLEAN ROOM TEST TO PREVENT OPTICAL CAVITY CONTAMINATION. REMOVE ONLY WHEN READY TO ASSEMBLE.

3. SINGLEMODE IDENTIFIER.

4. FOR USE AT BOTH 1310 AND 1550nm WAVELENGTHS.

1515739-1

PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN E. HOPKINS 08OCT2002

CHK D. WERTMAN 08OCT2002

APVD D. WERTMAN 08OCT2002

PRODUCT SPEC -

APPLICATION SPEC -

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

MATERIAL
STAINLESS
ALLOYS & NBRFINISH
N/A
-

TE Connectivity

NAME
INSERT ASSEMBLY, PRO BEAM JR.,
2x1310/1550nm SM

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 00779 C-1515739

SCALE 4:1 SHEET 1 OF 1 REV F

1470-19 (3/13)