

AMP | LEAVYSEAL

TE Internal #: 2112233-1

Automotive Connector Caps & Covers, Cover - Cable Exit, Cable Exit Angle 90°, Black, PA GF, 46 Position, -40 – 248 °F [-40 – 120 °C],

LEAVYSEAL

View on TE.com >



Connectors > Automotive Connectors > Automotive Connector Accessories > Automotive Connector Caps & Covers > LEAVYSEAL Backshells











Protection & Strain Relief Accessory Type: Cover - Cable Exit

Cable Exit Angle: 90°
Strain Relief: With

Primary Product Color: Black
Primary Product Material: PA GF

All LEAVYSEAL Backshells (13)

Features

Product Type Features

Protection & Strain Relief Accessory Type	Cover - Cable Exit
Configuration Features	
Number of Positions	46
Body Features	
Cable Exit Angle	90°
Primary Product Color	Black
Primary Product Material	PA GF
Mechanical Attachment	
Strain Relief	With
Dimensions	
Compatible Cable Bundle Diameter Range	26 mm[1.024 in]

Usage Conditions



Compatible With Connector Style	Housing For Female Terminals
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Industry Standards	
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	500
Packaging Method	Box
Other	
Serviceable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts









Also in the Series | LEAVYSEAL



Automotive Connector Caps & Covers



Automotive Housings(72)



Insertion & Extraction Tools(5)



Other Automotive Connector Accessories(15)



Customers Also Bought



LEAVYSEAL Backshells



TE Part #1-2299782-1 8POS,MIXED,REC HSG,ASSY,SLD



TE Part #3-2112231-2 46POS,AMP MCP1.5K,REC HSG,ASSY



TE Part #1418916-1 MULTI CORE CABLE APAPTER 180 DEGREE













Documents

Product Drawings
COVER,90,FOR 46POS

English

CAD Files

Customer View Model

ENG_CVM_CVM_2112233-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2112233-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2112233-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

German

Automotive Connector Caps & Covers, Cover - Cable Exit, Cable Exit Angle 90°, Black, PA GF, 46 Position, -40 – 248 °F [-40 – 120 °C], LEAVYSEAL

