



**STRIPPING DIMENSIONS**

- (b) NOTES:**
1. MATERIAL: COPPER ALLOY
  2. PLATING:  
ITEM 1: 30µin HARD GOLD over min. 50µin NICKEL  
ITEM 2: GOLD FLASH over NICKEL  
ITEM 3: NICKEL PLATED
  3. CRIMPING: USE CRIMP TOOL 360X10409X  
WITH TOOL INSERT 360X20029X  
SELECTOR SETTINGS: 3 FOR AWG 16  
2 FOR AWG 18  
2 FOR AWG 20

Directive 2002/95/EC RoHS compliant

(b)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish: SEE NOTES				tolerance ISO 2768-m		dim. in mm		scale: 5:1	
								material: SEE NOTES	
				date		name		title:	
				drawn 23.03.98		Barcinski		High Power Contact male Crimp version 10A Hochstromkontaktstift	
				appd. 23.03.98		Mickenbecker			
				norm					
				d-old				dwg no: Inventor 10	
3 x b		Ä3854		19.01.2011		K.H.		DIN-A4	
a		Origin						sh: 1	
rev.		description		date		name		part no: 131C11019X	



title:		High Power Contact male Crimp version 10A Hochstromkontaktstift	
dwg no:		Inventor 10	
part no:		131C11019X	