



Product: 6509UE ☑

Security & Sound, #22-12c, BC, CMP

Product Description

Security & Sound Cable, Plenum-CMP 12-22 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:	Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls
Construction Details	

Element No. of Elements Size Stranding Material Conductor(s) 12 22 7x30 BC - Bare Copper

Insulation

Conductor

Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
PVC - Polyvinyl Chloride	0.008 in (0.20 mm)	0.047 in (1.2 mm)	Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple, Gray, Pink, Tan

Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.015 in (0.38 mm)	0.217 in	Yes

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
17.41 Ohm/1000ft	27.5 pF/ft (90.2 pF/m)	1.4 Amps per Conductor at 25°C

Voltage



Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C To +75°C

Bend Radius

Stationary Min. Ins	tallation Min.
y Win. Ins	tanation Mil
17 in (FF 1 mans) 0.1	7 in
2.17 in (55.1 mm) 2.13	/ in
Max. Pull Tension:	
nax. I dii Terision.	
Bulk Cable Weight:	
ŭ	

Standards and Compliance

Environmental Suitability:	Outdoor

Flammability / Reaction to Fire:	NFPA 262 (UL910), FT6	
CPR Compliance:	CPR Euroclass: Eca	
NEC / UL Compliance:	Article 800, CMP	
CEC / C(UL) Compliance:	CMP	
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
UK Regulation Compliance:	UKCA Mark	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	
Non-Plenum Number:	5509UE	

History

Update and Revision:	Revision Number: 0.302 Revision Date: 05-05-2023

Part Numbers

Variants

Item #	Color	UPC	Footnote
6509UE 8771000	Natural	612825178057	С
6509UE 877U1000	Natural	612825178040	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.