



RGE



Aerosusa.com  
 service@aerosusa.com  
 855.393.9905

Metal connector, safety-type, straight, metric outer thread, incl. special sealing, brass thrust collar and O-ring, for EMC applications

Material: Nickel-plated brass

Temperature:  
 -40°C ... +120°C  
 -40°F ... +248°F

Protection Class: IP 66

Properties:

- Highly watertight and dustproof
- Friction-type locking of conduit and screw
- Connector correct grounding
- Covered conduit ends
- Vibration- and tension proof

### CERTIFICATIONS



*"Unsurpassed in Cable Protection and Strain Relief"*

2409 Herr St.  
 Harrisburg, PA 17103



Aerosusa.com  
service@aerosusa.com  
855.393.9905

## Technical Data Sheet

Product #	Thread	Trade Size	AD	Conduit ID (in)	Conduit OD (in)	I (in)	B (in)	C (in)	D (in)	WS1 (in)	WS2 (in)	lb/100	PU
5126.013.012	M12 x 1.5	5/16"	13	0.39	0.55	0.35	1.1	0.39	1.1	0.75	0.83	4.6297	10 PC
5126.015.016	M16 x 1.5	3/8"	15.8	0.47	0.67	0.51	1.14	0.39	1.14	0.91	0.98	7.2752	10 PC
5126.021.020	M20 x 1.5	1/2"	21.2	0.63	0.91	0.65	1.22	0.39	1.18	1.06	1.14	8.5980	10 PC
5126.034.032	M32 x 1.5	1"	34.5	1.08	1.42	1.08	1.57	0.51	1.57	1.69	1.77	24.2508	10 PC
5126.042.040	M40 x 1.5	1 1/4"	42.5	1.4	1.73	1.4	1.57	0.51	1.57	2.05	2.13	32.8488	10 PC
5126.054.050	M50 x 1.5	1 1/2"	54.5	1.85	2.2	1.75	1.85	0.55	1.85	2.05	2.6	47.3993	10 PC

*"Unsurpassed in Cable Protection and Strain Relief"*

2409 Herr St.  
Harrisburg, PA 17103