ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00024	Connector, dc plug, 5.5x2.1xL23 mm, molding style, spring contacts	1	
2	50-00025	Connector, dc jack, 5.5x2.1xL17.4 mm, molding style	2	
3	30-00683	Wire, 2C TS, 18 AWG, UL2464, 300V, 80C, 5.2 mm, VW-1, PVC	1	
4	24-00182	Overmold, dc plug, 5.5 mm, Tensility, black	1	black
5	24-00183	Overmold, dc jack, 5.5 mm, Tensility, black	1	black



Notes:
Functionally equivalent components may be substituted

Electrical requirements: 7 A, 48 Vdc

Wiring Diagram		
50-00024	wire color	50-00025
center	red	center
sleeve	black	sleeve

Revision:	Date:	Description:
A	9/13/2016	Initial release

Prepared: JD Digitally signed by JD Date: 2022.12.20 14:20:13 -08'00'

Verified: PB Digitally signed by PB Date: 2022.12.20 14:23:09 -08'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:

RoHS and REACH compliant

Function test: no open, no short circuit, no intermittent

Description:

Cable, 1830 mm, 5.5x2.1x12mm 50-00024 plug to 5.5x2.1mm 50-00025 jack, 18 AWG, 30-00683 wire

TENSILITY

tel 1.541.323.3228 *800* 877.670.7118
fax 1.541.323.4202 *web* tensility.com

Size: A

Part number: 10-02229

Scale: 1:1

Sheet 1 of 1

5 4 3 2 1