NOTE: ALL MATERIAL COMPLIANT ROHS STANDARD

L+Tmm

33.3

13.0

③

②

①

8

1

11.7

6.5

Color:Transparent

MARKING: SLIM SERIES CAT6A 28AWG UTP CM PVC

A

A

34.0

②

③

①

1

8

Color:Transparent

13.8

6.6

6.5

JACKET:PVC Thickness:0.60±0.1mm
OD=3.6±0.15mm

INSULATION:HDPE ThIckness:0.3±0.05mm
OD=0.61±0.05mm

CONDUCTOR:28AWG(7/0.12±0.008mmBC)*4P

SEC:A-A

orange 1 | green 2
white/orange | white/orange

blue 3 | brown 4
white/blue | white/brown

Cable Part No. Color Guide *Replace "XX" in the Part No. to the respective color code (e.x. CM-100250GNBSTK for a Green cable)*

| White = **WT** | Gray = **GY** | Black = **BK** | Blue = **BL** | Green = **GN** |
| Purple = **PU** | Yellow = **YW** | Orange = **OR** | Red = **RD** | |

Cable Part No.
Length Guide

0.5ft. CM-100250XXBSTK	**7ft.** CM-100258XXBSTK
1ft. CM-100251XXBSTK	**10ft.** CM-100261XXBSTK
1.5ft. CM-100252XXBSTK	**15ft.** CM-100263XXBSTK
2ft. CM-100253XXBSTK	**20ft.** CM-100264XXBSTK
3ft. CM-100254XXBSTK	**30ft.** CM-100265XXBSTK
5ft. CM-100256XXBSTK	**50ft.** CM-100267XXBSTK

L(ft)	T(inch)	T(%)	L(ft)	T(inch)	T(%)
0.5	±1.2	20%	12	±2	1.39%
1	±1.2	10%	15	±3.15	1.75%
1.5	±1.2	6.6%	20	±4	1.67%
2	±1.2	5%	25	±4	1.33%
3	±1.2	3.33%	30	±6	1.67%
4	±1.2	2.5%	40	±6	1.25%
5	±1.2	2%	50	±6	1.0%
6	±1.2	1.67%	60	±6	1.0%
7	±2	2.38%	70	±6	0.67%
8	±2	2.08%	80	±6	0.59%
9	±2	1.85%	90	±6	0.5%
10	±2	1.67%	100	±6	0.5%

PINOUT		
P1	WIRE	P2
1	WHITE/ORANGE	1
2	ORANGE	2
3	WHITE/GREEN	3
6	GREEN	6
5	WHITE/BLUE	5
4	BLUE	4
7	WHITE/BROWN	7
8	BROWN	8

CABLE**MAX**

③	RJ45 PLUG	8P8C 50U" GOLD PLATED TWO-PIECE PLUG.		
②	MOLDED	PVC SHORT MOLDED BOOT		
①	CABLE	CAT6A UTP 4P/28AWG(7/0.12±0.008MM BC) OD=3.6±0.15mm		
NO.	PART NAME	SPECIFICATION DESCRIPTION	QT'Y	UNIT

Drawn By:	Date: 10 / 31 / 2022	Description: Cat.6A Slim Cables 28AWG
Checked By:	Sheet 1 of 1	Model No. CM-1002XXXXBSTK
Approved By:	Scale 1:1	Rev. 01	Unit: mm