

International **IR** Rectifier

PD - 95251A

IRF7353D1PbF


FETKY™ MOSFET / Schottky Diode

- Co-packaged HEXFET® Power MOSFET and Schottky Diode
- Ideal For Buck Regulator Applications
- N-Channel HEXFET
- Low V_F Schottky Rectifier
- Generation 5 Technology
- SO-8 Footprint
- Lead-Free


Description

The **FETKY** family of co-packaged MOSFETs and Schottky diodes offers the designer an innovative, board space saving solution for switching regulator and power management applications. Generation 5 HEXFET Power MOSFETs utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. Combining this technology with International Rectifier's low forward drop Schottky rectifiers results in an extremely efficient device suitable for use in a wide variety of portable electronics applications.

The SO-8 has been modified through a customized leadframe for enhanced thermal characteristics. The SO-8 package is designed for vapor phase, infrared or wave soldering techniques.



$V_{DSS} = 30V$
 $R_{DS(on)} = 0.029\Omega$
 Schottky $V_f = 0.39V$



Absolute Maximum Ratings ($T_A = 25^\circ C$ unless otherwise noted)

Parameter	Maximum	Units
$I_D @ T_A = 25^\circ C$	Continuous Drain Current	A
$I_D @ T_A = 70^\circ C$		
I_{DM}	Pulsed Drain Current ①	W
$P_D @ T_A = 25^\circ C$		
$P_D @ T_A = 70^\circ C$	Power Dissipation	
	Linear Derating Factor	mW/ $^\circ C$
V_{GS}	Gate-to-Source Voltage	V
dv/dt	Peak Diode Recovery dv/dt ②	V/ns
T_J, T_{STG}	Junction and Storage Temperature Range	$^\circ C$

Thermal Resistance Ratings

Parameter	Maximum	Units
$R_{\theta JA}$	62.5	$^\circ C/W$

Notes:

- ① Repetitive rating; pulse width limited by maximum junction temperature (see figure 9)
- ② Starting $T_J = 25^\circ C$, $L = 10mH$, $R_G = 25\Omega$, $I_{AS} = 4.0A$
- ③ $I_{SD} \leq 4.0A$, $di/dt \leq 74A/\mu s$, $V_{DD} \leq V_{(BR)DSS}$, $T_J \leq 150^\circ C$
- ④ Surface mounted on FR-4 board, $t \leq 10sec$.

IRF7353D1PbF

International
Rectifier

MOSFET Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

Parameter		Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	30	—	—	V	$V_{\text{GS}} = 0\text{V}$, $I_D = 250\mu\text{A}$
$R_{\text{DS}(\text{on})}$	Static Drain-to-Source On-Resistance	—	0.023	0.032	Ω	$V_{\text{GS}} = 10\text{V}$, $I_D = 5.8\text{A}$
		—	0.032	0.046		$V_{\text{GS}} = 4.5\text{V}$, $I_D = 4.7\text{A}$
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	1.0	—	—	V	$V_{\text{DS}} = V_{\text{GS}}$, $I_D = 250\mu\text{A}$
g_f	Forward Transconductance	—	14	—	S	$V_{\text{DS}} = 24\text{V}$, $I_D = 5.8\text{A}$
I_{DSS}	Drain-to-Source Leakage Current	—	—	1.0	μA	$V_{\text{DS}} = 24\text{V}$, $V_{\text{GS}} = 0\text{V}$
		—	—	25		$V_{\text{DS}} = 24\text{V}$, $V_{\text{GS}} = 0\text{V}$, $T_J = 55^\circ\text{C}$
I_{GSS}	Gate-to-Source Forward Leakage	—	—	100	nA	$V_{\text{GS}} = 20\text{V}$
	Gate-to-Source Reverse Leakage	—	—	-100		$V_{\text{GS}} = -20\text{V}$
Q_g	Total Gate Charge	—	22	33	nC	$I_D = 5.8\text{A}$
Q_{gs}	Gate-to-Source Charge	—	2.6	3.9		$V_{\text{DS}} = 24\text{V}$
Q_{gd}	Gate-to-Drain ("Miller") Charge	—	6.4	9.6		$V_{\text{GS}} = 10\text{V}$ (see figure 8)
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	—	8.1	12	ns	$V_{\text{DD}} = 15\text{V}$
t_r	Rise Time	—	8.9	13		$I_D = 1.0\text{A}$
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	—	26	39		$R_G = 6.0\Omega$
t_f	Fall Time	—	17	26		$R_D = 15\Omega$
C_{iss}	Input Capacitance	—	650	—	pF	$V_{\text{GS}} = 0\text{V}$
C_{oss}	Output Capacitance	—	320	—		$V_{\text{DS}} = 25\text{V}$
C_{rss}	Reverse Transfer Capacitance	—	130	—		$f = 1.0\text{MHz}$ (see figure 7)

MOSFET Source-Drain Ratings and Characteristics

Parameter		Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	—	—	2.5	A	
I_{SM}	Pulsed Source Current (Body Diode)	—	—	30		
V_{SD}	Body Diode Forward Voltage	—	0.78	1.0	V	$T_J = 25^\circ\text{C}$, $I_S = 1.7\text{A}$, $V_{\text{GS}} = 0\text{V}$
t_{rr}	Reverse Recovery Time (Body Diode)	—	45	68	ns	$T_J = 25^\circ\text{C}$, $I_F = 1.7\text{A}$
Q_{rr}	Reverse Recovery Charge	—	58	87	nC	$dI/dt = 100\text{A}/\mu\text{s}$ ③

Schottky Diode Maximum Ratings

	Parameter	Max.	Units	Conditions	
$I_{\text{F(av)}}$	Max. Average Forward Current	2.7	A	50% Duty Cycle. Rectangular Wave, $T_A = 25^\circ\text{C}$ See Fig. 14	
		1.9		$T_A = 70^\circ\text{C}$	
I_{SM}	Max. peak one cycle Non-repetitive Surge current	120	A	5μs sine or 3μs Rect. pulse	Following any rated load condition & with V_{RRM} applied
		11		10ms sine or 6ms Rect. pulse	

Schottky Diode Electrical Specifications

	Parameter	Max.	Units	Conditions	
V_{FM}	Max. Forward voltage drop	0.50	V	$I_F = 1.0\text{A}$, $T_J = 25^\circ\text{C}$	
		0.62		$I_F = 2.0\text{A}$, $T_J = 25^\circ\text{C}$	
		0.39		$I_F = 1.0\text{A}$, $T_J = 125^\circ\text{C}$	
		0.57		$I_F = 2.0\text{A}$, $T_J = 125^\circ\text{C}$.	
I_{RM}	Max. Reverse Leakage current	0.06	mA	$V_R = 30\text{V}$	$T_J = 25^\circ\text{C}$
		16			$T_J = 125^\circ\text{C}$
C_t	Max. Junction Capacitance	92	pF	$V_R = 5\text{Vdc}$ (100kHz to 1 MHz) 25°C	
dv/dt	Max. Voltage Rate of Change	3600	V/μs	Rated V_R	

Power Mosfet Characteristics




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance
Vs. Temperature

IRF7353D1PbF

International
Rectifier

Power Mosfet Characteristics




Fig 5. Typical On-Resistance Vs. Drain Current




Fig 6. Typical On-Resistance Vs. Gate Voltage




Fig 7. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 8. Typical Gate Charge Vs. Gate-to-Source Voltage

Power Mosfet Characteristics




Fig 9. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient




Fig 10. Typical Source-Drain Diode Forward Voltage

IRF7353D1PbF
Schottky Diode Characteristics

International
IR Rectifier




Fig. 12 -Typical Forward Voltage Drop Characteristics




Fig. 13 - Typical Values of Reverse Current Vs. Reverse Voltage





Fig.14 - Maximum Allowable Ambient Temp. Vs. Forward Current


SO-8 (Fetky) Package Outline (Dimensions are shown in millimeters (inches)



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.0532	.0688	1.35	1.75
A1	.0040	.0098	0.10	0.25
b	.013	.020	0.33	0.51
c	.0075	.0098	0.19	0.25
D	.189	.1968	4.80	5.00
E	.1497	.1574	3.80	4.00
e	.050	BASIC	1.27	BASIC
e1	.025	BASIC	0.635	BASIC
H	.2284	.2440	5.80	6.20
K	.0099	.0196	0.25	0.50
L	.016	.050	0.40	1.27
y	0°	8°	0°	8°


NOTES:

1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
2. CONTROLLING DIMENSION: MILLIMETER
3. DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
5. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.15 (.006).
6. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.25 (.010).
7. DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE.



SO-8 (Fetky) Part Marking Information

EXAMPLE: THIS IS AN IRF7807D1 (FETKY)




IRF7353D1PbF

International
IR Rectifier


SO-8 (Fetky) Tape and Reel

Dimensions are shown in millimeters (inches)



NOTES:

1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



NOTES :

1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Data and specifications subject to change without notice.
This product has been designed and qualified for the Consumer market.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105

TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information. 10/04

www.irf.com