



### RESISTANCE VS TEMPERATURE CHARACTERISTICS:

Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)	Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)
-40	291.2	304.4	318.1	50	3.49	3.561	3.634
-35	213.6	222.6	231.9	55	2.879	2.944	3.01
-30	158.3	164.4	170.8	60	2.388	2.446	2.505
-25	118.4	122.6	127	65	1.989	2.041	2.095
-20	89.39	92.32	95.34	70	1.664	1.711	1.759
-15	68.17	70.21	72.31	75	1.399	1.44	1.483
-10	52.38	53.81	55.27	80	1.18	1.217	1.256
-5	40.53	41.53	42.55	85	1.001	1.034	1.069
0	31.58	32.27	32.98	90	0.853	0.882	0.913
5	24.72	25.2	25.69	95	0.729	0.756	0.783
10	19.48	19.82	20.15	100	0.625	0.649	0.674
15	15.46	15.68	15.91	105	0.539	0.56	0.582
20	12.33	12.49	12.64	110	0.465	0.484	0.504
25	9.9	10	10.1	115	0.403	0.42	0.438
30	7.955	8.053	8.151	120	0.351	0.366	0.382
35	6.427	6.52	6.613	125	0.306	0.32	0.334
40	5.218	5.304	5.392	130	0.261	0.274	0.286
45	4.257	4.337	4.417	135	0.216	0.228	0.238

### NOTES:

1. RESISTANCE @ 25°C : 10KΩ±2%
2. BETA VALUE (0/50°C) : 3892K±1%
3. OPERATING TEMPERATURE RANGE : -40°C TO +135°C.
4. DISSIPATION FACTOR : 1.5mW/°C
5. THERMAL TIME CONSTANT : LESS THAN 3SECONDS IN WATER
- 6.INSULATION RESISTANCE : 10MΩ AT 100 VDC

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		<b>molex</b>					
	△/A = 0	mm NTS								
DIVISIONAL SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 657230 DRWN: RAVIKM CHK'D: RBBHASKAR APPR: RBBHASKAR		PRODUCT CUSTOMER DRAWING					
	△/E = 0	ANGULAR TOL ± °								
DIVISIONAL SYMBOLS	△/V = 0	4 PLACES ±	INITIAL REVISION: DRWN: RAVIKM APPR: RBBHASKAR		DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION	
		3 PLACES ±			2152725607		PSD	000	A	
		2 PLACES ±			2021/03/03		MATERIAL NUMBER		CUSTOMER	SHEET NUMBER
		1 PLACE ±			2021/03/05		2152725607		OTS	1 OF 1
	0 PLACES ±	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES				
					A3-SIZE	215272				