

Coupling relay - PSR-PS20-1NO-1NC-24DC-DUMMY - 2702346

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling relay for SIL 3 high and low-demand applications, couples digital output signals to the I/O, 1 enabling current path, 1 confirmation current path, 1 digital signal output, safe state off applications, test pulse filter, fixed screw terminal block

The illustration shows the standard type

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	60.000 g
Custom tariff number	90230080
Country of origin	Germany

Technical data

Input data

Rated control circuit supply voltage U_s	24 V DC
--	---------

Output data

Contact type	1 enabling current path
	1 confirmation current path

General

Net weight	48.7 g
------------	--------

Connection data

Connection method	Screw connection
pluggable	no

Coupling relay - PSR-PS20-1NO-1NC-24DC-DUMMY - 2702346

Classifications

eCl@ss

eCl@ss 5.1	27371901
eCl@ss 6.0	27371819
eCl@ss 8.0	27371819
eCl@ss 9.0	27371819

ETIM

ETIM 5.0	EC001449
----------	----------