

4916 Series

6 Digit Non-Reset Counter



The 4916 Series incorporates the latest manufacturing technology together with basic design to achieve high performance over a wide temperature range with low power consumption. These counters can be mounted by two front flange styles, base mount or behind the panel (front mount). The 4916 has UL approvals and can operate over a wide voltage range of DC or AC power.

The compact design and various mounting styles make it the ideal counter for almost all counting applications. This electro-mechanical counter will not lose its count during power failures or from electrical noise.

Key Features

- Low cost, large quantity discounts
- Patented high-performance mechanism
- UL and cUL approved (49 Series)
- Rugged plastic package
- Wide range of voltages available
- Long life

Applications

- Mail Equipment
- Photo Machines
- Vending Machines
- Gaming Machines
- Elevators
- Copy Machines
- Ticket Machines

Specifications

Display	6 Digit, white on black, 0.160" figures
Operating Voltage ±10%	DC: 5, 12, 24, 48, 110, 125 (2W) AC: 24, 48, 120, 230 (5VA)
Reset	None
Count Speed	10 CPS, standard. 50/50 ratio on/off.
Max. On Time	Infinite
Temperature	Storage: 14°F to 122°F (-10°C to +50°C) Operating: 23°F to 104°F (-5°C to +40°C)
Approvals	UL# and cUL# E36690
Termination	UL/cUL wire leads, 11" long, standard
Weight	4.0oz (113g)

Part Number Ordering Chart


Example:

R 9 - 49 1 6 AD


Mounting						
D	D-Base Mount (Front/H-Base Mount)					
R	Behind the Panel Mount (Front)					
P	Panel Mount (Flange 1.81"x1.81")					
FL	Flange Mount (1.53"x1.8)					
RV	Combo Front/V-Base Mount					
OR	Special Metal D - Base Mount					
Voltage						
1	230 VAC					
2	120 VAC					
3	24 VAC					
7	110 VDC					
8	24 VDC					
9	12 VDC					
11	5 VDC					
12	125 VDC					
14	48 VDC					
23	9 VDC					
Product Number						
49	Product Number					
Reset						
1	Non-reset					
# of Figures						
6	6 Figure					
Suffix						
Blank	Counter Set at 999800 (Standard)					
A	Counter Set at 000000					
B	Counter Set at 999980					
C	24" Lead Wires					
D	Diode Suppression					
E	16" Lead Wires					

Dimensions


D - D-Base Mount




V - V-Base Mount / RV- Combo Front / V-Base Mount




R- Behind The Panel Mount (Front)




FL - Panel Mount (Flange FL) 1.535 x 1.8 (39 x 45.7) P - Panel Mount (Flange) 1.81 x 1.81(46 x 46)



OR - Front / Base Combo Mount (Front)



Panel Cutout



Part Number Ordering Chart

FL1-4916	230VAC, 6 figures, panel mount	R9-4916AD	12VDC, 6 figures, rear mount, w/diode, set @ 000000
FL2-4916	120VAC, 6 figures, panel mount	RV1-4916	230VAC, 6 figures, front & V-base mount
FL3-4916	24VAC, 6 figures, panel mount	RV2-4916	120VAC, 6 figures, front & V-base mount
FL7-4916CD	110VDC, 6 figures, panel mount, w/diode, 24" LDS	RV3-4916	24VAC, 6 figures, front & V-base mount
FL8-4916D	24VDC, 6 figures, panel mount, w/diode	RV8-4916	24VDC, 6 figures, front & V-base mount
R11-4916D	5VDC, 6 figures, front mount, w/diode	RV9-4916	12VDC, 6 figures, front & V-base mount
R2-4916	120VAC, 6 figures, rear mount	RV11-4916	5VDC, 6 figures, front & V-base mount
R8-4916	24VDC, 6 figures, rear mount	RV2-4916B	120VAC, 6 figures, V-base mount, set @ 999980
R14-4916	48VDC, 6 figures, rear mount		



Trumeter (The Americas)
6601 Lyons Rd, Suite H-7
Coconut Creek, Florida
FL 33073,
USA
Tel: +1 954 725 6699
Email: sales.usa@trumeter.com

Trumeter (Europe)
Pilot Mill
Alfred Street
Bury,
BL9 9JR
Tel: +44 161 674 0960
Email: sales.uk@trumeter.com

Innovative Design Technologies Sdn. Bhd
Lot 5881, Lorong Iks Bukit Minyak 1
Taman Perindustrian Iks, 14000 Bukit Tengah
Penang, Malaysia
Web: www.idtworld.com
Tel: + 604 5015700
Email: sales.my@idtworld.com