

Product data sheet

Specifications



set of 4 Spacial SF M12 lifting eyebolt - galvanized cast steel



NSYSFEB

Overview

Lead time Usually Ships within 4 Weeks

Main

Bereich	Spacial
Kategorie	Lifting accessory
Product or component type	Lifting eye
Anwendung	Multi-purpose
Mounting location	Enclosure top
Mounting support	Directly in the axis of the uprights
Range compatibility	Spacial (Spacial SF) Spacial (Spacial SFHD) Prisma (Prisma PH) Spacial (Spacial SFM)
Device composition	4 eyebolt
Quantity per set	Set of 1

Complementary

Material	Cast steel
Surface finish	Galvanized
Fixing mode	Screwed
Permanent permissible load	340 kg for 1 eyebolt vertical direction
Height	62.5 mm
Width	55 mm
Depth	24 mm
Diameter	29 mm
ISO thread	M12

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.000 cm

Package 1 Width	10.000 cm
Package 1 Length	10.500 cm
Package 1 Weight	771.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	18.924 kg
Unit Type of Package 3	P12
Number of Units in Package 3	192
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	163.392 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)