



DRIVER, PUNCH 230V AC ADAPTER

Punch Driver w/230 VAC Adapter

Cat No: LS60LA230

UPC No: 783310521624

Description

- State of the art 18V lithium ion (Li-ion) battery provides 70% more cycles per charge and faster cycle times
- LED light provides the operator with the battery charge and tool maintenance status
- Forward handle position improves tool balance
- One trigger controls all tool functions
- Punching cycle stops automatically when hole is complete to prevent damage to punch
- Overmolded tacky grip areas make gripping the tool easier and more comfortable
- LED work light illuminates dark work areas
- Greenlee battery-powered crimping tools now use bio-degradable oil
- Smart chargers control the charging current, charging voltage and battery temperature to maximize battery life
- 10~ Available with 120V, 12V or 230V battery charger or with 120V or 230V corded adapter in place of batteries and charger

Specifications

- Battery : 18 V, 3.0 AMP-HR Lithium-Ion
- Battery Charge Time : 1 HR
- Height : 12.500 IN (318.000 MM)
- Includes : "1614SS UPC 30043 Draw Stud 3/8" x 2-13/16", 31872 UPC 31872 Draw Stud 3/4" x 4-1/8", 1924AA UPC 03248 Spacer-Short, 33967 UPC 33967 Stud Adapter 3/8", 01686 UPC 01686 Metal Case, MKLS60 UPC 05956 Case for LS60 "
- Maximum Punch Force : 6.7 TON (60 KN)
- Maximum Ram Travel : 0.870 IN (22.000 MM)
- Maximum Rectangular Punch Size : 1.378 X 2.559 IN (35.000 X 65.000 MM)
- Maximum Round Punch Size : 2.420 IN Diameter (61.500 MM)
- Maximum Square Punch Size : 2-11/16 X 2-11/16 IN (68.000 X 68.000 MM)
- Overall Length Ram Retracted : 11.500 IN (292.000 MM)
- Type : Battery Powered, Knockout Punch
- Weight : 8.800 LB (4.000 KG)