



Main

Range	ClimaSys
Product name	ClimaSys CR
Product or Component Type	Ultra thin resistance heater
Power range	50 W
Input voltage	240 V AC 50/60 Hz
Electrical connection	Cable 6.56 ft (2 m)

Complementary

Operating position	Vertical Horizontal
Ambient Air Temperature for Operation	-76...158 °F (-60...70 °C)
Temperature setting range	-40...158 °F (-40...70 °C)
Material	Silicone rubber
Height	External 7.87 in (200 mm)
Width	External 12.60 in (320 mm)
Depth	External 0.06 in (1.6 mm)
Device composition	6 self-adhesive Velcro pads 6 plastic spacers 4 Telequick nuts 4 clip-on nuts Fixing accessories
Condition of use	Heaters must be installed with a thermal controller Electrical protection is needed Air sealed enclosure
Fixing Mode	By 4 screws
Mounting Support	Telequick mounting plate DIN rail Adhesive Velcro Standard mounting plate

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES 1
GTIN	3606480530166
Nbr. of units in pkg.	1
Package weight(Lbs)	15.52 oz (440.0 g)
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.97 in (5.0 cm)
Package 1 width	12.80 in (32.5 cm)
Package 1 Length	13.78 in (35.0 cm)
Unit Type of Package 2	PAM
Number of Units in Package 2	180
Package 2 Weight	202.83 lb(US) (92.0 kg)
Package 2 Height	70.87 in (180.0 cm)
Package 2 width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------