### S20L0C-P09MCC0-520S

series\_l, type\_s2




#### **General information**

| Part number       | S20L0C-P09MCC0-520S |         |
|-------------------|---------------------|---------|
| Termination       | solder              |         |
| Size              | 0                   | CALCO   |
| Locking principle | push                | C HALLS |
| Coding            | 0_key               |         |
| Cable Diameter    | cable_mini_52       |         |
| Cable outlet      | bend_relief         |         |







# Contact insert description

| Number of contacts   | 9      |
|----------------------|--------|
| Contact type         | pins   |
| Contact diameter     | 05mm   |
| Insulator material   | peek   |
| Wire cross section   | 28_awg |
| Termination          | solder |
| Termination diameter | 04mm   |

reverse\_gender\_on\_request

#### **Technical information**

| Max. creepage and air clearance distance | 04_mm    | 08_mm         |
|--|----------|---------------|
| Nominal current single contact           | 04_a     | iec_60512_5_2 |
| Nominal current insert                   | 2,6 A    | vde_0298_4    |
| Test voltage                             | 06_kv_ac | sae_13441     |
|  |          |               |

safety\_text

## Mechanical and environmental data

| Degree of protection* | ip50     |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles         | 5000     |

mated\_unmated

#### Material and surface treatments

| Housing | m_chrome      |
|---------|---------------|
| Contact | cu_alloy_gold |

safety\_text\_2 ul\_text illustrative\_text