1.5 METERS LENGTH



Connector A 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel 50 Ohm RG-316 Continuity/Hi-Pot Connector B FA1-NZSJ-C01-0 FAKRA Jack Straight Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A			Cable		Connector B		
De Tyj Ge Bo Co Po Im Mc Bo Bo IP Co Co Co Ma	rt #: 112234	D JK RG188 500 • Mount er	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-316 RG-316 - ST 0.102 ST Braid 0.102 50 Ohm None Continuity Hi-Pot 1.5 Meters	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Material: Max. Freq.: Booting: Clocking:	FA1-NZSJ-C01-0 FAKRA-Z JK RG174 FAKRA Jack Straight Crimp Standard 50 Ohm Cable Brass Nickel None Beryllium Copper Gold 3 GHz FAKRA-Z Jack Strait 0°		
Amphenol CUSTOM CABLE		PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE V CUSTOM CABLE INC. ACCEPTA	HIS DRAWING MAY CONTAIN PATENTED OR COPRIETARY INFORMATION AND MUST NOT BE USED OR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE IC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED I ANY FORM WITHOUT THE WRITTEN CONSENT OF USTOM CABLE INC. ACCEPTANCE OF THIS DRAWING STABLISHES AND AGREEMENT OF THE FOREGOING.		Title: BNC-ST-JK/FKRAZ-ST-JK G316 1.5M Part No: Q-0405E00051.5M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	