TE Internal #: 1-50871-8

Pin Sockets, Socket Length 7.32 mm [.288 in], PCB Hole Diameter . 101 in [2.56 mm], Open Bottom, $1.31-2.08~\rm mm^2$ Wire Size, 16-14

AWG Wire Size

View on TE.com >



Connectors > Socket Connectors > Pin Sockets > Miniature Spring Sockets: Open Bottom, Beryllium Copper, 7.5A











Socket Length: **7.32 mm [.288 in]**

PCB Hole Diameter: 2.56 mm [.101 in]

Socket Sleeve Style: Open Bottom

Wire Size: 1.31 – 2.08 mm²

All Miniature Spring Sockets: Open Bottom, Beryllium Copper, 7.5A (9)

Features

Product Type Features

Socket Sleeve Style	Open Bottom
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Body Features

Sleeve Material	Copper
Sleeve Plating Material	Gold Flash over Nickel

Contact Features

Contact Spring Plating Material	Gold
Contact Spring Plating Thickness	.762 μm[30 μin]
Contact Mating Area Plating Material Thickness	30 μm[30 μin]
Contact Base Material	Beryllium Copper



Contact Current Rating (Max)	7.5 A
Termination Features	
Insertion Method	Hand/Semi-Automatic
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Termination Method to Wire & Cable	Solder
Dimensions	
PCB Thickness (Recommended)	.79 – 3.18 mm[.031 – .125 in]
Socket Length	7.32 mm[.288 in]
PCB Hole Diameter	2.56 mm[.101 in]
Wire Size	1.31 – 2.08 mm²
Mating Pin Diameter Range	1.42 – 1.65 mm[.056 – .065 in]
Usage Conditions	
Operating Temperature Range	-65 – 125 °C[-85 – 257 °F]
Operation/Application	
Solder Process Feature	None
Circuit Application	Power & Signal
Packaging Features	
Packaging Quantity	2000
Packaging Method	Bag, Loose Piece
Other	
Spring Material	Beryllium Copper

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Pin-in-Paste capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought















TE Part #1-1415033-1 RY6120244 Pin Sockets, Socket Length 7.32 mm [.288 in], PCB Hole Diameter .101 in [2.56 mm], Open Bottom, 1.31 – 2.08 mm² Wire Size, 16 – 14 AWG Wire Size



TE Part #8-1415032-1 RY6120054

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-50871-8_W.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-50871-8_W.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-50871-8_W.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Product Specifications

Application Specification

English