# 2103247-5 ACTIVE

#### HVA 280

TE Internal #: 2103247-5

PCB Mount Header, Vertical, Wire-to-Device, Fully Shrouded,

Silver, Through Hole - Press-Fit, Sealable, Signal, Orange, HVA 280

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > High-Voltage Header



Connector System: Wire-to-Device

Sealable: Yes

PCB Mount Orientation: Vertical
Primary Product Color: Orange
Mating Tab Width: 2.8 mm [.11 in]

All High-Voltage Header (34)

### **Features**

### **Product Type Features**

Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Header
Header Type	Fully Shrouded
Connector System	Wire-to-Device
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

PCB Mount Orientation	Vertical	
-----------------------	----------	--

### **Electrical Characteristics**

Voltage Rating (Max)	750 VDC
Nominal Voltage Architecture	750 V
Operating Voltage	750 VDC

### **Body Features**

Primary Product Color	Orange
Connector & Keying Code	E

## **Contact Features**



Contact Type	Tab
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.8 mm[.031 in]
Contact Mating Area Plating Material	Silver
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
Mounting Holes	Without
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Dimensions	
Connector Length	45.4 mm[1.78 in]
Connector Width	40.6 mm[1.59 in]
Usage Conditions	
Operating Temperature (Max)	65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C, 140 °C[149 °F][158 °F][167 °F][176 °F][185 °F] [194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F][284 °F]
Operating Temperature Range	-40 - 140 °C[-40 - 284 °F]
Operation/Application	
Shielded	Yes
Circuit Application	Signal
Industry Standards	
Degree of Protection	IP67
UL Flammability Rating	None
Packaging Features	
Packaging Type	Box

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)  Candidate List Declared Against: JUNE 2023 (235)  SVHC > Threshold:  Octamethylcyclotetrasiloxane (D4) (.5% in Component Part)  Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part)  Decamethylcyclopentasiloxane (D5) (.5% in Component Part)  Article Safe Usage Statements:  Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



Also in the Series | HVA 280





Automotive Connector Caps & Covers (5)



Automotive Connector EMC Shielding (15)



Automotive Housings(78)



Connector Seals & Cavity Plugs(8)



Electric, Hybrid & Fuel Cell Cable Assemblies(6)



High Voltage Wire Processing Equipment(7)



Other Automotive Connector Accessories(37)



PCB Headers & Receptacles(37)

# Customers Also Bought



TE Part #2103245-4 Inner Housing, Split Hdr, Key D, HVA280



TE Part #1-794220-0 MINI UMNL2 PIN 22-18 AWG AU



TE Part #2103247-4 High-Voltage Header



TE Part #2-2141600-2
TAB 2.8x0.8 CONTACT CF SRC Ag



TE Part #1534594-1 MCON 1.2 CB REC SRC SN



TE Part #794197-1 10P MINI UMNL2 CAP HSG UL94V0



TE Part #2103245-1 Inner Housing, Split Hdr, Key A, HVA280

TE Part #YPROTERRA-DT-COMPL
DT KIT COMPLETE

### **Documents**

### **Product Drawings**

SPLIT HEADER ASSY, KEY E, HVA280

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_2103247-5\_A.2d\_dxf.zip

English

3D PDF

PCB Mount Header, Vertical, Wire-to-Device, Fully Shrouded, Silver, Through Hole - Press-Fit, Sealable, Signal, Orange, HVA 280



3D

**Customer View Model** 

ENG\_CVM\_CVM\_2103247-5\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2103247-5\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Instruction Sheets** 

Instruction Sheet (U.S.)

English