



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .125 (3.175mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .030 (.762mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)									
AP(R, L)-04-18-9	.062 (1.57mm)	.874 (22.2mm)	4.125 (104.775mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-04-18-0	.062 (1.57mm)	.874 (22.2mm)	4.125 (104.775mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-06-18-9	.062 (1.57mm)	1.500 (38.1mm)	6.187 (157.149mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-06-18-0	.062 (1.57mm)	1.500 (38.1mm)	6.187 (157.149mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-08-18-9	.062 (1.57mm)	2.187 (55.5mm)	8.187 (207.949mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2
AP(R, L)-08-18-0	.062 (1.57mm)	2.187 (55.5mm)	8.187 (207.949mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	AH-2



ADVANCED CABLE TIES – 18 LB. (80n) MINIATURE SERIES CABLE TIES

COLOR DESIGNATIONS:

0 = UV BLACK 9 = NATURAL

MATERIAL:

NYLON 6/6 POLYAMIDE

B	4/27/17	JA	KT	KT	NEW LOGO ADDED.	SHEET 1 OF 1	REV.: B	DRAWING NO.: 18-B			
A	12/22/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE		
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	4/27/17	KT	NONE		

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.82.1