



SS Stainless Steel

Inch table

Dimensions in: inches - millimeters

¹ d ₁	² d ₂ Thread	³ Length l			d ₃	b	h ₁	h ₂	t min.
1.02 26	10 x 32	.39 10	.63 16	-	.39 10	.43 11	.39 10	.18 4.5	.31 8
1.02 26	1/4 x 20	.63 16	.79 20	.98 25	.39 10	.43 11	.39 10	.18 4.5	.31 8
1.34 34	1/4 x 20	.79 20	.98 25	1.18 30	.47 12	.51 13	.47 12	.20 5	.39 10
1.34 34	5/16 x 18	.63 16	.79 20	1.18 30	.47 12	.51 13	.47 12	.20 5	.39 10

Metric table

Dimensions in: millimeters - inches

¹ d ₁	² d ₂ Thread	³ Length l			d ₃	b	h ₁	h ₂	t min.
26 1.02	M 4	-	-	-	10 .39	11 .43	10 .39	4.5 .18	7 .28
26 1.02	M 5	10 .39	16 .63	-	10 .39	11 .43	10 .39	4.5 .18	8 .31
26 1.02	M 6	16 .63	20 .79	25 .98	10 .39	11 .43	10 .39	4.5 .18	8 .31
34 1.34	M 6	20 .79	25 .98	30 1.18	12 .47	13 .51	12 .47	5 .20	10 .39
34 1.34	M 8	16 .63	20 .79	30 1.18	12 .47	13 .51	12 .47	5 .20	9 .35

Specification

- Stainless steel precision casting
European Standard No. 1.4308 (AISI CF-8)
Matte shot-blasted finish **MT**
- RoHS compliant

Information

Where a greater torque is required GN 434 wing nuts and GN 433 wing screws are a better solution than knurled nuts.

see also...

- Wing Nuts GN 834 (Stainless Steel)
- Wing Screws GN 835 (Stainless Steel)
- Hand Knobs DIN 6335 (Stainless Steel)

How to order (Inch wing nut)	¹ Handle diameter d ₁
¹ ² ⁴ GN 434-34-1/4X20-MT	² Thread d ₂
	⁴ Finish

How to order (Metric wing screw)	¹ Handle diameter d ₁
¹ ² ³ ⁴ GN 433-26-M6-16-MT	² Thread d ₂
	³ Length l
	⁴ Finish