





8-BIT MAGNITUDE COMPARATORS

The SN54/74LS682, 684, 688 are 8-bit magnitude comparators. These device types are designed to perform comparisons between two eight-bit binary or BCD words. All device types provide $P = Q$ outputs and the LS682 and LS684 have $P > Q$ outputs also.

The LS682, LS684 and LS688 are totem pole devices. The LS682 has a 20 k Ω pullup resistor on the Q inputs for analog or switch data.

CONNECTION DIAGRAMS (TOP VIEW)




5

**SN54/74LS682
SN54/74LS684
SN54/74LS688**

8-BIT MAGNITUDE COMPARATORS

LOW POWER SCHOTTKY



ORDERING INFORMATION

SN54LSXXXJ Ceramic
 SN74LSXXXN Plastic
 SN74LSXXXDW SOIC

FUNCTION TABLE

DATA	INPUTS		OUTPUTS	
	\overline{G}, GT	$G2$	$P = Q$	$P > Q$
$P = Q$	L	L	L	H
$P > Q$	L	L	H	L
$P < Q$	L	L	H	H
X	H	H	H	H

H = HIGH Level, L = LOW Level, X = Irrelevant

SN54/74LS682 • SN54/74LS684 • SN54/74LS688

GUARANTEED OPERATING RANGES

Symbol	Parameter		Min	Typ	Max	Unit
V _{CC}	Supply Voltage		54 74	4.5 4.75	5.0 5.0	V
T _A	Operating Ambient Temperature Range		54 74	-55 0	25 25	°C
I _{OH}	Output Current — High		54, 74			-0.4 mA
I _{OL}	Output Current — Low		54 74			12 24 mA


DC CHARACTERISTICS OVER OPERATING TEMPERATURE RANGE (unless otherwise specified)

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
V _{IH}	Input HIGH Voltage	2.0			V	Guaranteed Input HIGH Voltage for All Inputs
V _{IL}	Input LOW Voltage	54		0.7	V	Guaranteed Input LOW Voltage for All Inputs
		74		0.8		
V _{IK}	Input Clamp Diode Voltage		-0.65	-1.5	V	V _{CC} = MIN, I _{IN} = -18 mA
V _{OH}	Output HIGH Voltage	54	2.5	3.5	V	V _{CC} = MIN, I _{OH} = MAX, V _{IN} = V _{IH} or V _{IL} per Truth Table
		74	2.7	3.5	V	
V _{OL}	Output LOW Voltage	54, 74	0.25	0.4	V	I _{OL} = 12 mA
		74	0.35	0.5	V	I _{OL} = 24 mA
I _{IH}	Input HIGH Current			20	µA	V _{CC} = MAX, V _{IN} = 2.7 V
		LS628-Q Inputs		0.1	mA	V _{CC} = MAX, V _{IN} = 5.5 V
		Others		0.1	mA	V _{CC} = MAX, V _{IN} = 7.0 V
I _{IL}	Input LOW Current	LS628-Q Inputs		-0.4	mA	V _{CC} = MAX, V _{IN} = 0.4 V
		Others		-0.2	mA	
I _{OS}	Short Circuit Current (Note 1)	-30		-130	mA	V _{CC} = MAX
I _{CC}	Power Supply Current	LS682		70	mA	V _{CC} = MAX
		LS684		65	mA	
		LS688		65	mA	

Note 1: Not more than one output should be shorted at a time, nor for more than 1 second.


SN54/74LS682 • SN54/74LS684 • SN54/74LS688

LOGIC DIAGRAMS



5

SN54/74LS682 thru LS684



SN54/74LS688

SN54/74LS682•SN54/74LS684•SN54/74LS688

AC CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

SN54/74LS682

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
t_{PLH} t_{PHL}	Propagation Delay, P to $\bar{P} = Q$		13 15	25 25	ns	$V_{CC} = 5.0 \text{ V}$ $C_L = 45 \text{ pF}$ $R_L = 667 \Omega$
t_{PLH} t_{PHL}	Propagation Delay, Q to $\bar{P} = \bar{Q}$		14 15	25 25	ns	
t_{PLH} t_{PHL}	Propagation Delay, P to $P > Q$		20 15	30 30	ns	
t_{PLH} t_{PHL}	Propagation Delay, Q to $P > Q$		21 19	30 30	ns	

SN54/74LS684

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
t_{PLH} t_{PHL}	Propagation Delay, P to $\bar{P} = Q$		15 17	25 25	ns	$V_{CC} = 5.0 \text{ V}$ $C_L = 45 \text{ pF}$ $R_L = 667 \Omega$
t_{PLH} t_{PHL}	Propagation Delay, Q to $\bar{P} = \bar{Q}$		16 15	25 25	ns	
t_{PLH} t_{PHL}	Propagation Delay, P to $P > Q$		22 17	30 30	ns	
t_{PLH} t_{PHL}	Propagation Delay, Q to $P > Q$		24 20	30 30	ns	

SN54/74LS688

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
t_{PLH} t_{PHL}	Propagation Delay, P to $\bar{P} = Q$		12 17	18 23	ns	$V_{CC} = 5.0 \text{ V}$ $C_L = 45 \text{ pF}$ $R_L = 667 \Omega$
t_{PLH} t_{PHL}	Propagation Delay, Q to $\bar{P} = \bar{Q}$		12 17	18 23	ns	
t_{PLH} t_{PHL}	Propagation Delay, $\bar{G}, \bar{G1}$ to $P = Q$		12 13	18 20	ns	