



General ordering data

Order No.	4061200000
Part designation	SSS Relais 60V/24V 2Adc
Version	Solid-state relay, 3...33 Vdc , 2 A DC , Plug-in connection
EAN	4032248415090
Qty.	1 pc(s).

Approvals

Approvals institutes



Control side

Rated control voltage	35 V DC.....72 V DC
-----------------------	---------------------

General data

Ambient temperature (operational)	-20 °C...+60 °C
Storage temperature	-40 °C...+70 °C
Climate	40°C/93% rel. humidity, no condensation
Weight	3.65 g
Connection system	Plug-in connection

Insulation coordination (EN 50 178)

Dielectric strength for control side - load side	2.5 kV
--	--------

Load side

Nominal switching current	2 A DC
Nominal switching voltage	3...33 Vdc
Status indicator	No

Classifications

ETIM 2.0	EC001504
ETIM 3.0	EC001504
eClass 4.1	27-27-09-00
eClass 5.0	27-27-09-90
eClass 5.1	27-27-09-90

Similar products

Order No.	Part designation	Version
8633000000	MOS 5Vdc / 24Vdc 2A	Solid-state relay, 3...33 V DC , 2 A , Screw connection
8632990000	MOZ 5Vdc / 24Vdc 2A	Solid-state relay, 3...33 V DC , 2 A , Tension clamp connection
8607350000	MOS 24Vdc / 24Vdc 2A	Solid-state relay, 3 V...33 V DC , 2 A , Screw connection
8607370000	MOZ 24Vdc / 24Vdc 2A	Solid-state relay, 3 V...33 V DC , 2 A , Tension clamp connection
8975200000	MOS 48VUC/24VDC 2A	Solid-State Relay, 3...33 V DC , 2 A , Screw connection
8607700000	MOS 120Vuc / 24Vdc 2A	Solid-state relay, 3 V...33 V DC , 2 A , Screw connection
8607740000	MOZ 120Vuc / 24Vdc 2A	Solid-state relay, 3 V...33 V DC , 2 A , Tension clamp connection
8607720000	MOS 230Vac / 24Vdc 2A	Solid-state relay, 3 V...33 Vdc , 2 A , Screw connection
8607760000	MOZ 230Vac / 24Vdc 2A	Solid-state relay, 3 V...33 Vdc , 2 A , Tension clamp connection
4061190000	SSS Relais 24V/24V 2Adc	Solid-state relay, 3...33 Vdc , 2 A DC , Plug-in connection