

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 5-position, Plug straight M8, coding: B, connected with unwired, on Socket straight M8, cable length: 2 m

Your advantages

- Easy and safe: 100% electrically tested plug-in components

Commercial data

Item number	1423839
Packing unit	1 pc
Minimum order quantity	50 pc
Note	Made to order (non-returnable)
Sales key	BF01
Product key	BF1BDA
GTIN	4055626356822
Weight per piece (including packing)	67.8 g
Weight per piece (excluding packing)	67.6 g
Customs tariff number	85444290
Country of origin	PL

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Technical data

Product properties

Product type	Sensor/actuator cable
Number of positions	5
No. of cable outlets	1
Shielded	no
Coding	B

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Nominal voltage U_N	30 V AC
	30 V DC
Nominal current I_N	3 A
Protective circuit	unwired

Signaling

Status display	No
Status display present	No

Connector

Connection 1

Type	Plug straight M8
Number of positions	5
Coding type	B
Number of positions	5

Connection 2

Type	Socket straight M8
Number of positions	5
	5

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Cable/line

Cable length	2 m
PUR, black, 5th conductor gray [115]	
Cable weight	30 kg/km
UL AWM Style	20549
Number of positions	5
Shielded	no
Cable type	PUR, black, 5th conductor gray [115]
Conductor structure signal line	32x 0.10 mm
AWG signal line	24
Conductor cross section	0.25 mm ²
Wire diameter incl. insulation	1.17 mm ±0.02 mm
External cable diameter	4.7 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material, filler	PP
Material wire insulation	PP
Single wire, color	brown, white, blue, black, gray
Thickness, insulation	approx. 0.21 mm (Core insulation) approx. 0.7 mm (Outer cable sheath)
Overall twist	5 cores, twisted
Length of twist, overall twist	75 mm
Max. conductor resistance	≤ 75 Ω/km
Insulation resistance	≥ 1 GΩ*km
Nominal voltage, cable	≤ 300 V (AC)
Test voltage	≥ 3000 V (AC)
Smallest bending radius, fixed installation	23.5 mm
Smallest bending radius, movable installation	47 mm
Max. bending cycles	4000000
Halogen-free	in accordance with DIN VDE 0472 part 815 in accordance with DIN EN 50267-2-1
Flame resistance	according to UL 758/1581 (horizontal) in accordance with UL 758/1581 FT2
Resistance to oil	According to DIN EN 60811-2-1, 168 h at 100°C
Other resistance	hydrolysis and microbe resistant Resistant to salt water Low adhesion abrasion-resistant
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -25 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Standards and regulations

Standard designation	M8 connector
Standards/specifications	IEC 61076-2-104

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable

1423839


<https://www.phoenixcontact.com/us/products/1423839>

Drawings

Circuit diagram



Schematic diagram




Pin assignment, socket side, M8, 5-pos., B-coded

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable

1423839


<https://www.phoenixcontact.com/us/products/1423839>

Dimensional drawing



Socket M8 x 1, straight

Schematic diagram



Pin assignment, pin side, M8, 5-pos., B-coded


SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Dimensional drawing



M8 x 1 male plug, straight version

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable





1423839

<https://www.phoenixcontact.com/us/products/1423839>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1423839>

 UL Listed Approval ID: FILE E 221474				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	3 A	-	-

 cUL Listed Approval ID: FILE E 221474				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	3 A	-	-

cULus Listed				
---------------------	--	--	--	--

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 8.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Accessories

PROT-M 8 FS-PA-CHAIN - Sealing cap

1430857

<https://www.phoenixcontact.com/us/products/1430857>

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 plugs



PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/us/products/1013779>

Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20



SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

PABA YE/23 - Insert label

1013782

<https://www.phoenixcontact.com/us/products/1013782>



Insert label, Strip, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/us/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

PROT-M 8 MS-PA-CHAIN - Screw plug

1430860

<https://www.phoenixcontact.com/us/products/1430860>

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 sockets



TSD 02 SAC - Torque screwdriver

1208487

<https://www.phoenixcontact.com/us/products/1208487>

Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors



SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

SAC BIT M8-D10 - Tool

1208461

<https://www.phoenixcontact.com/us/products/1208461>



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com