

Specification Sheet

Part Number: 157-00329

Offset mount allows wire or cable to be attached beside mounting hole instead of directly above it.

Reusable fastener can be extracted from threaded or nonthreaded holes using a 5/16" hex driver.

Delivers high extraction force for reliable performance, yet it's easy to install.

Heat stabilized material provides excellent resistance to high temperatures.



Blind Hole Mount Cable Tie, Offset, 8"L, 0.25" Thread/Non-Thread Hole, 50lb, PA66HS, Black, 500/bg

Article Number 157-00329

Type T50ROSBHMBSO18

Color Black (BK)

Quantity Per bag

Product Description Blind Hole Mount Offset Cable Ties secure bundles beside the mounting hole instead of directly above it. The unique design includes a heat stabilized cable tie and formula-matched, hex-head fastener that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or non-threaded blind holes. Since cable or wire bundle is beside the fastener, the assembly can be removed using a hex driver from the mounting hole without cutting the cable tie. The fastener can then be reused.

| | |
|-------------------------------------|--|
| Short Description | Blind Hole Mount Cable Tie, Offset, 8"L, 0.25" Thread/Non-Thread Hole, 50lb, PA66HS, Black, 500/bg |
| Global Part Name | T50ROSBHMBSO18-PA66HS-BK |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225.0 |
| Length L (Imperial) | 8.0 |
| Length L (Metric) | 203.2 |
| Offset Length (Imperial) | 0.71 |
| Offset Length (Metric) | 18.0 |
| Fixation Method | Blind Plug |
| Identification Plate Position | none |
| Releasable Closure | No |
| Width W (Imperial) | 0.185 |
| Width W (Metric) | 4.7 |
| Bundle Diameter Min (Imperial) | 0.08 |
| Bundle Diameter Min (Metric) | 2.0 |
| Bundle Diameter Max (Imperial) | 1.97 |

| | |
|---|--|
| Bundle Diameter Max (Metric) | 50.0 |
| Height H (Imperial) | 0.736 |
| Height H (Metric) | 18.7 |
| Diameter D (Imperial) | 0.25 |
| Diameter D (Metric) | 6.35 |
| Mounting Hole Diameter D (Imperial) | 0.25 |
| Mounting Hole Diameter D (Metric) | 6.35 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.246 |
| Mounting Hole Diameter D Max (Imperial) | 0.254 |
| Mounting Hole Diameter D Max (Metric) | 6.45 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +257°F (-40°C to +125°C) |

| | |
|------------------------------|------------|
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)