


PART NO. SEE CHART
SDA-2599-NA*



RECOMMENDED PC BOARD HOLE DIMENSIONS

SEE NOTE 1
SLIGHT SAW BURR PERMITTED ON TOP & SIDE EDGES - BOTH ENDS

FOR VOID LOC. SEE CHART ON SHEET 2

- NOTES:
- A) 1. PIN PUSH OUT FORCE: 3 LBS. MIN.
 2. BURRS NOT TO EXTEND BELOW SURFACE D
 - C. CODE LETTER PRECEDING PART NO. INDICATES MFG LOCATION I - IRELAND
 - * PARTS TO MEET MOLEX PRODUCT SPEC 0-39

10-19-1181	A-2599-18A	18	3.400	3.568	
1171	A-2599-17A	17	3.200	3.368	
1161	A-2599-16A	16	3.000	3.168	
1151	A-2599-15A	15	2.800	2.968	
1141	A-2599-14A	14	2.600	2.768	
1131	A-2599-13A	13	2.400	2.568	
1121	A-2599-12A	12	2.200	2.368	
1111	A-2599-11A	11	2.000	2.168	
1101	A-2599-10A	10	1.800	1.968	
1091	A-2599-9A	9	1.600	1.768	
1081	A-2599-8A	8	1.400	1.568	
1071	A-2599-7A	7	1.200	1.368	
1061	A-2599-6A	6	1.000	1.168	
1051	A-2599-5A	5	.800	.968	
1041	A-2599-4A	4	.600	.768	
1031	A-2599-3A	3	.400	.568	
10-19-1021	A-2599-2A	2	.200	.368	
PART NO	ENG NO	NO OF CIRCUITS	DIM. A	DIM. B	

WAFER MATERIAL: NYLON-NATURAL COLOR

.200 CENTER DISTANCE

ISSUED SHEET 2
ADD PARTS/VOIDS
EAO # 16533
9-17-79
BIT REC WAFER
1580X 7-10-78
C/A WAS 1.005
C/A WAS 1.004
WAS 0.8 PER EC
LAP 1.1
8.000 ± .010
3/5-72 JLL/ER
ALANDED NOTE 1
ECO # 612
4-3-72 TFS/ER
2-2-72 HJ/BAW
REVISIONS

SCALE 14X	POLARIZING WAFER ASSEMBLY	
	MOLEX PRODUCTS CO.	DATE: 1-13-72
HC	DOWNERS GROVE, ILL. 60513, U.S.A.	SHEET 2 OF 2 SDA-2599-NA*
	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO THE MOLEX PRODUCTS COMPANY AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	

SEE CHART
 SOA-2599-NA-X

FOR DIMENSIONS SEE SHEET 'J'

VOID LOC	PART No	ENG. No.	NO OF CKTS
5	I 10-19-1062	A-2599-6A-5	6
2, 4, 6, 8 E10	I 10-19-1112	A-2599-11A-51	11
2, 4, 7	I 10-19-1082	A-2599-8A-51	B

FILMED

FOR REVISION
 SEE SHEET A

REVISION

POLARIZING WAVE ASSEMBLY
 200 CENTER DISTANCE
 SOLE INCO. POLARIZING
 9-17-79
 SEE CHART SOA-2599-NA-X