

FMC7G15US60

Compact & Complex Module

General Description

Fairchild's Insulated Gate Bipolar Transistor (IGBT) power modules provide low conduction and switching losses as well as short circuit ruggedness. They are designed for applications such as motor control, uninterrupted power supplies (UPS) and general inverters where short circuit ruggedness is a required feature.

Features


- UL Certified No. E209204
- Short circuit rated 10us @ $T_C = 100^\circ\text{C}$, $V_{GE} = 15\text{V}$
- High speed switching
- Low saturation voltage : $V_{CE}(\text{sat}) = 2.2\text{V}$ @ $I_C = 15\text{A}$
- High input impedance
- Built in brake and 3 phase rectifier circuit
- Fast & soft anti-parallel FWD

Applications

- AC & DC motor controls
- General purpose inverters
- Robotics
- Servo controls



Package Code : 21PM-AA



Internal Circuit Diagram

Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ unless otherwise noted

| | Symbol | Description | FMC7G15US60 | Units |
|------------------|-------------|---|-------------|----------------------|
| Inverter & Brake | V_{CES} | Collector-Emitter Voltage | 600 | V |
| | V_{GES} | Gate-Emitter Voltage | ± 20 | V |
| | I_C | Collector Current @ $T_C = 25^\circ\text{C}$ | 15 | A |
| | $I_{CM(1)}$ | Pulsed Collector Current | 30 | A |
| | I_F | Diode Continuous Forward Current @ $T_C = 100^\circ\text{C}$ | 15 | A |
| | I_{FM} | Diode Maximum Forward Current | 30 | A |
| | P_D | Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$ | 45 | W |
| Converter | T_{SC} | Short Circuit Withstand Time @ $T_C = 100^\circ\text{C}$ | 10 | us |
| | V_{RRM} | Repetitive Peak Reverse Voltage | 1200 | V |
| | I_O | Average Output Rectified Current | 20 | A |
| | I_{FSM} | Surge Forward Current @ 1Cycle at 60Hz, Peak value Non-Repetitive | 200 | A |
| Common | I^2t | 1 Cycle Surge Current | 164 | A^2s |
| | T_J | Operating Junction Temperature | -40 to +150 | $^\circ\text{C}$ |
| | T_{STG} | Storage Temperature Range | -40 to +125 | $^\circ\text{C}$ |
| Mounting Torque | V_{ISO} | Isolation Voltage @ AC 1minute | 2500 | V |
| | | Mounting part Screw @ M4 | 1.25 | N.m |

Notes :

(1) Repetitive rating : Pulse width limited by max. junction temperature

Electrical Characteristics of the IGBT @ Inverter & Brake $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Units |
|------------------------------|---|---------------------------------|------|------|-----------|---------------------|
| Off Characteristics | | | | | | |
| BV_{CES} | Collector-Emitter Breakdown Voltage | $V_{GE} = 0V, I_C = 250\mu A$ | 600 | -- | -- | V |
| $\Delta BV_{CES}/\Delta T_J$ | Temperature Coeff. of Breakdown Voltage | $V_{GE} = 0V, I_C = 1mA$ | -- | 0.6 | -- | V/ $^\circ\text{C}$ |
| I_{CES} | Collector Cut-Off Current | $V_{CE} = V_{CES}, V_{GE} = 0V$ | -- | -- | 250 | μA |
| I_{GES} | G-E Leakage Current | $V_{GE} = V_{GES}, V_{CE} = 0V$ | -- | -- | ± 100 | nA |

| | | | | | | |
|---------------------------|---|-------------------------------|-----|-----|-----|---|
| On Characteristics | | | | | | |
| $V_{GE(th)}$ | G-E Threshold Voltage | $I_C = 15mA, V_{CE} = V_{GE}$ | 5.0 | 6.0 | 8.5 | V |
| $V_{CE(sat)}$ | Collector to Emitter Saturation Voltage | $I_C = 15A, V_{GE} = 15V$ | -- | 2.2 | 2.8 | V |

| | | | | | | |
|--------------------------------|------------------------------|--|----|-----|----|----|
| Dynamic Characteristics | | | | | | |
| C_{ies} | Input Capacitance | $V_{CE} = 30V, V_{GE} = 0V,$ $f = 1MHz$ | -- | 948 | -- | pF |
| C_{oes} | Output Capacitance | | -- | 101 | -- | pF |
| C_{res} | Reverse Transfer Capacitance | | -- | 33 | -- | pF |

| | | | | | | |
|----------------------------------|------------------------------|---|------|------|-----|----|
| Switching Characteristics | | | | | | |
| $t_{d(on)}$ | Turn-On Delay Time | $V_{CC} = 300V, I_C = 15A,$ $R_G = 13\Omega, V_{GE} = 15V,$ Inductive Load, $T_C = 25^\circ\text{C}$ | -- | 17 | -- | ns |
| t_r | Rise Time | | -- | 33 | -- | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | -- | 44 | 65 | ns |
| t_f | Fall Time | | -- | 118 | 200 | ns |
| E_{on} | Turn-On Switching Loss | | -- | 0.32 | -- | mJ |
| E_{off} | Turn-Off Switching Loss | | -- | 0.36 | -- | mJ |
| E_{ts} | Total Switching Loss | -- | 0.68 | 0.95 | mJ | |
| $t_{d(on)}$ | Turn-On Delay Time | $V_{CC} = 300V, I_C = 15A,$ $R_G = 13\Omega, V_{GE} = 15V,$ Inductive Load, $T_C = 125^\circ\text{C}$ | -- | 20 | -- | ns |
| t_r | Rise Time | | -- | 34 | -- | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | -- | 48 | 70 | ns |
| t_f | Fall Time | | -- | 212 | 350 | ns |
| E_{on} | Turn-On Switching Loss | | -- | 0.34 | -- | mJ |
| E_{off} | Turn-Off Switching Loss | | -- | 0.7 | -- | mJ |
| E_{ts} | Total Switching Loss | -- | 1.04 | 1.45 | mJ | |
| T_{sc} | Short Circuit Withstand Time | $V_{CC} = 300V, V_{GE} = 15V$ @ $T_C = 100^\circ\text{C}$ | 10 | -- | -- | us |
| Q_g | Total Gate Charge | $V_{CE} = 300V, I_C = 15A,$ $V_{GE} = 15V$ | -- | 42 | 60 | nC |
| Q_{ge} | Gate-Emitter Charge | | -- | 7 | 10 | nC |
| Q_{gc} | Gate-Collector Charge | | -- | 17 | 24 | nC |

Electrical Characteristics of the DIODE @ Inverter & Brake $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Units | |
|----------|-------------------------------------|--|---------------------------|------|------|-------|----|
| V_{FM} | Diode Forward Voltage | $I_F = 15\text{A}$ | $T_C = 25^\circ\text{C}$ | -- | 1.9 | 2.8 | V |
| | | | $T_C = 100^\circ\text{C}$ | -- | 2.0 | -- | |
| t_{rr} | Diode Reverse Recovery Time | | $T_C = 25^\circ\text{C}$ | -- | 75 | 130 | ns |
| | | | $T_C = 100^\circ\text{C}$ | -- | 100 | -- | |
| I_{rr} | Diode Peak Reverse Recovery Current | $I_F = 15\text{A}$ $di/dt = 30\text{ A/us}$ | $T_C = 25^\circ\text{C}$ | -- | 1.0 | 1.8 | A |
| | | | $T_C = 100^\circ\text{C}$ | -- | 1.3 | -- | |
| Q_{rr} | Diode Reverse Recovery Charge | | $T_C = 25^\circ\text{C}$ | -- | 40 | 100 | nC |
| | | | $T_C = 100^\circ\text{C}$ | -- | 70 | -- | |

Electrical Characteristics of the DIODE @ Converter $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Units | |
|-----------|----------------------------|--------------------|---------------------------|------|------|-------|----|
| V_{FM} | Diode Forward Voltage | $I_F = 20\text{A}$ | $T_C = 25^\circ\text{C}$ | -- | 1.1 | 1.5 | V |
| | | | $T_C = 100^\circ\text{C}$ | -- | 1.0 | -- | |
| I_{RRM} | Repetitive Reverse Current | $V_R = V_{RRM}$ | $T_C = 25^\circ\text{C}$ | -- | -- | 8 | mA |
| | | | $T_C = 100^\circ\text{C}$ | -- | 5 | -- | |

Thermal Characteristics

| | Symbol | Parameter | Typ. | Max. | Units |
|-----------|-----------------|---|------|------|--------------------|
| Inverter | $R_{\theta JC}$ | Junction-to-Case (IGBT Part, per 1/6 Module) | -- | 2.77 | $^\circ\text{C/W}$ |
| | $R_{\theta JC}$ | Junction-to-Case (DIODE Part, per 1/6 Module) | -- | 3.5 | $^\circ\text{C/W}$ |
| Brake | $R_{\theta JC}$ | Junction-to-Case (IGBT Part) | -- | 2.77 | $^\circ\text{C/W}$ |
| | $R_{\theta JC}$ | Junction-to-Case (DIODE Part) | -- | 3.5 | $^\circ\text{C/W}$ |
| Converter | $R_{\theta JC}$ | Junction-to-Case (DIODE Part, per 1/6 Module) | -- | 2.7 | $^\circ\text{C/W}$ |
| Weight | | Weight of Module | 60 | -- | g |




Fig 1. Typical Output Characteristics




Fig 2. Typical Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case Temperature at Variant Current Level




Fig 4. Load Current vs. Frequency




Fig 5. Saturation Voltage vs. V_{GE}




Fig 6. Saturation Voltage vs. V_{GE}




Fig 7. Capacitance Characteristics




Fig 8. Turn-On Characteristics vs. Gate Resistance




Fig 9. Turn-Off Characteristics vs. Gate Resistance




Fig 10. Switching Loss vs. Gate Resistance




Fig 11. Turn-On Characteristics vs. Collector Current




Fig 12. Turn-Off Characteristics vs. Collector Current




Fig 13. Switching Loss vs. Collector Current




Fig 14. Gate Charge Characteristics




Fig 15. SOA Characteristics




Fig 16. Turn-Off SOA Characteristics




Fig 17. RBSOA Characteristics




Fig 18. Transient Thermal Impedance




Fig 19. Forward Characteristics





Fig 20. Reverse Recovery Characteristics

Package Dimension

21PM-AA (FS PKG CODE BJ)



Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

| | | | | |
|----------------------------------|---------------------------------|---------------------------------|-----------------------------|------------------|
| ACE _x [™] | FAST [®] | OPTOLOGIC [™] | SMART START [™] | VCX [™] |
| Bottomless [™] | FAST _r [™] | OPTOPLANAR [™] | STAR*POWER [™] | |
| CoolFET [™] | FRFET [™] | PACMAN [™] | Stealth [™] | |
| CROSSVOLT [™] | GlobalOptoisolator [™] | POP [™] | SuperSOT [™] -3 | |
| DenseTrench [™] | GTO [™] | Power247 [™] | SuperSOT [™] -6 | |
| DO _M E [™] | HiSeC [™] | PowerTrench [®] | SuperSOT [™] -8 | |
| EcoSPARK [™] | ISOPLANAR [™] | QFET [™] | SyncFET [™] | |
| E ² CMOS [™] | LittleFET [™] | QS [™] | TruTranslation [™] | |
| EnSigna [™] | MicroFET [™] | QT Optoelectronics [™] | TinyLogic [™] | |
| FACT [™] | MicroPak [™] | Quiet Series [™] | UHC [™] | |
| FACT Quiet Series [™] | MICROWIRE [™] | SLIENT SWITCHER [®] | UltraFET [®] | |

STAR*POWER is used under license

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

| Datasheet Identification | Product Status | Definition |
|--------------------------|------------------------|---|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |