



Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207
Tel: 1-800-52 ALPHA (25742), Web: www.alphawire.com

Customer Specification

PART NO. 882260

Construction

		Diameters (In)
1) Component 1	60 X 1 COND	
a) Conductor	22 (7/30) AWG TC	0.030
b) Insulation	0.010" Wall, Nom. PVC, Semi Rigid	0.050
(1) Color Code	Alpha Wire Color Code F	

Cond	Color	Cond	Color	Cond	Color
1	BLACK	21	ORANGE/GREEN	41	GREEN/WHITE/BLUE
2	WHITE	22	BLACK/WHITE/RED	42	ORANGE/RED/GREEN
3	RED	23	WHITE/BLACK/RED	43	BLUE/RED/GREEN
4	GREEN	24	RED/BLACK/WHITE	44	BLACK/WHITE/BLUE
5	ORANGE	25	GREEN/BLACK/WHITE	45	WHITE/BLACK/BLUE
6	BLUE	26	ORANGE/BLACK/WHITE	46	RED/WHITE/BLUE
7	WHITE/BLACK	27	BLUE/BLACK/WHITE	47	GREEN/ORANGE/RED
8	RED/BLACK	28	BLACK/RED/GREEN	48	ORANGE/RED/BLUE
9	GREEN/BLACK	29	WHITE/RED/GREEN	49	BLUE/RED/ORANGE
10	ORANGE/BLACK	30	RED/BLACK/GREEN	50	BLACK/ORANGE/RED
11	BLUE/BLACK	31	GREEN/BLACK/ORANGE	51	WHITE/BLACK/ORANGE
12	BLACK/WHITE	32	ORANGE/BLACK/GREEN	52	RED/ORANGE/BLACK
13	RED/WHITE	33	BLUE/WHITE/ORANGE	53	GREEN/RED/BLUE
14	GREEN/WHITE	34	BLACK/WHITE/ORANGE	54	ORANGE/BLACK/BLUE
15	BLUE/WHITE	35	WHITE/RED/ORANGE	55	BLUE/BLACK/ORANGE
16	BLACK/RED	36	ORANGE/WHITE/BLUE	56	BLACK/ORANGE/GREEN
17	WHITE/RED	37	WHITE/RED/BLUE	57	WHITE/ORANGE/GREEN
18	ORANGE/RED	38	BLACK/WHITE/GREEN	58	RED/ORANGE/GREEN
19	BLUE/RED	39	WHITE/BLACK/GREEN	59	GREEN/BLACK/BLUE
20	RED/GREEN	40	RED/WHITE/GREEN	60	ORANGE/GREEN/BLUE
2) Cable Assembly		60 Components Cabled			

a) Twists:	1.8 Twists/foot (min)	
3) Jacket	0.035" Wall, Nom.,PVC	0.520 (0.547 Max.)
a) Color(s)	SLATE	
b) Print	ALPHA WIRE-* P/N 882260 60C 22 AWG (UL) TYPE CL2 90C OR AWM 2464 80C 300V C(RU) AWM II A/B 105C 300V FT4 CE ROHS * = Factory Code	

Applicable Specifications

1) UL	AWM/STYLE 2464	80°C / 300 V _{RMS}
	CL2	90°C
2) CSA International	C(RU) AWM II A/B	105°C / 300 V _{RMS}
	FT4	
3) CE:	EU Low Voltage Directive 2006/95/EC	

Environmental

1) CE: EU Directive 2011/65/EU(RoHS2):	
	This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C.
2) REACH Regulation (EC 1907/2006):	
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.

Properties

Physical & Mechanical Properties	
1) Temperature Range	-20 to 105°C
2) Bend Radius	10X Cable Diameter
3) Pull Tension	330 Lbs, Maximum
Electrical Properties (For Engineering purposes only)	
1) Voltage Rating	300 V _{RMS}
2) Capacitance	23.5 pf/ft @1 kHz, Nominal Conductor to Conductor
3) Inductance	0.18 µH/ft, Nominal
4) Conductor DCR	16.5 Ω/1000ft @20°C, Nominal

Other

Packaging	Flange x Traverse x Barrel (inches)
a) 1000 FT	30 x 14 x 12 Continuous length
b) 500 FT	20 x 11 x 8 Continuous length
c) 100 FT	16 x 11 x 8 Continuous length
d) Bulk(Made-to-order)	
	<i>[Spool dimensions may vary slightly]</i>

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207
Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire (“Alpha”) makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an “AS IS” basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY

Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. ©2013 ALPHA WIRE - all rights reserved.



EU/China ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: 882260

882260 , RoHS-Compliant Commencing With 7/1/2005 Production

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive, with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. The reader is referred to this Directive for the specific definitions and extents of this Directive. **No Exemptions are required for RoHS Compliance on this item.** It should be noted that this product does not fall within the scope of Directive 2011/65/EU, but this Certificate is offered for cases where this product will be used within EEE that does fit within the Directive's scope. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control of Pollution by Electronic Information Products" standard SJ/T 11364-2006.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) , Including Deca-BDE	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire Company:

Dave Watson, Director of Engineering & QA

4/30/2013