

Features

- Long operating life.
- Current driven devices.
- Different color available.
- Three Pieces of chip.
- Solid state high libration resistant.
- RoHS compliant.




ATTENTION
OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
DISCHARGE
SENSITIVE
DEVICES

Applications

- Used as indicator.
- System appliances, measuring instruments.

Package Schematics



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25(0.01") unless otherwise noted.
3. Specifications are subject to change without notice.

Absolute Maximum Ratings (T _A =25°C)[1]		Red (AlGaI nP)	Green (InGa N)	Blue (InG aN)	Unit
Reverse Voltage	V _R	5	5	5	V
Forward Current	I _F	30	20	30	mA
Forward Current (Peak) 1/10 Duty Cycle 0.1ms Pulse Width[3]	i _{FS}	200	100	100	mA
Power Dissipation [2]	P _D	300			mW
Operating Temperature	T _A	-40 ~ +85			°C
Storage Temperature	T _{stg}	-40 ~ +85			°C
Electrostatic Discharge Threshold(HBM)		3000	450	250	V
Lead Solder Temperature [2mm Below Package Base]		260°C For 3-5 Seconds			


Notes:

1. Limiting values given are in accordance with the absolute Maximum ratings, Stress above one and more of the values may cause permanent damage to the device.
2. Within 300mW at all chips are lightened
3. 1/10Duty Cycle, 0.1ms Pulse Width
4. A Relative Humidity between 40% and 60% is recommended in ESD-protected work areas to reduce static build up during assembly process (Reference JEDEC/JESD625-A and JEDEC/J-STD-033)





Operating Characteristics (T _A =25°C)		Red (AlGaI nP)	Green (InGa N)	Blue (InGa N)	Unit
Forward Voltage (Typ.) (I _F =20mA)	V _F	2.1	3.3	3.3	V
Forward Voltage (Max.) (I _F =20mA)	V _F	2.5	4.1	4.0	V
Reverse Current (Max.) (V _R =5V)	I _R	10	50	50	uA
Wavelength of Peak Emission CIE127-2007*(Typ.) (I _F =20mA)	λ _P	631*	515*	465*	nm
Wavelength of Dominant Emission CIE127-2007*(Typ.) (I _F =20mA)	λ _D	624*	525*	470*	nm
Spectral Line Full Width At Half-Maximum (Typ.) (I _F =20mA)	Δλ	20	35	22	nm
Capacitance (Typ.) (V _F =0V, f=1MHz)	C	25	45	100	pF

Part Number	Emitting Color	Emitting Material	Lens-color	Luminous Intensity CIE127-2007* ($I_F=20\text{mA}$) mcd		Wavelength CIE127-2007* nm λ_P	Description
				min.	typ.		
XKJZ07W-NV22ARD	Red	AlGaInP	Water Clear	300*	647*	631*	Common Anode
	Green	InGaN		300*	557*	515*	
	Blue	InGaN		80*	148*	465*	





*Luminous intensity value and wavelength are in accordance with CIE127-2007 standards.







❖ Red




❖ Green



❖ Blue



Wave Soldering Profile for Thru-Hole Products (Pb-Free Components)



Notes:

1. Recommend pre-heat temperature of 105°C or less (as measured with a thermocouple attached to the LED pins) prior to immersion in the solder wave with a maximum solder bath temperature of 260°C
2. Peak wave soldering temperature between 245°C ~ 255°C for 3 sec (5 sec max).
3. Do not apply stress to the epoxy resin while the temperature is above 85°C.
4. Fixtures should not incur stress on the component when mounting and during soldering process.
5. SAC 305 solder alloy is recommended.
6. No more than one wave soldering pass.
7. During wave soldering, the PCB top-surface temperature should be kept below 105°C.



Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity / luminous flux, or wavelength), the typical accuracy of the sorting process is as follows:

1. Wavelength: +/-1nm
2. Luminous Intensity / Luminous Flux: +/-15%
3. Forward Voltage: +/-0.1V

Note: Accuracy may depend on the sorting parameters.

PACKING & LABEL SPECIFICATIONS



TERMS OF USE

1. Data presented in this document reflect statistical figures and should be treated as technical reference only.
2. Contents within this document are subject to improvement and enhancement changes without notice.
3. The product(s) in this document are designed to be operated within the electrical and environmental specifications indicated on the datasheet.
 User accepts full risk and responsibility when operating the product(s) beyond their intended specifications.
4. The product(s) described in this document are intended for electronic applications in which a person's life is not reliant upon the LED. Please consult with a SunLED representative for special applications where the LED may have a direct impact on a person's life.
5. The contents within this document may not be altered without prior consent by SunLED.
6. Additional technical notes are available at <http://www.SunLEDusa.com/TechnicalNotes.asp>