0.75 METER LENGTH



Connector A 132116 SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-58 Continuity/Hi-Pot Connector B 252180 MCX Plug Straight Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| | Connector A | | | Cable | | Connector B | |
|----------|------------------------------|---|-------------|--|-------------------|--|--|
| Part #: | 132116 | | Part #: | RG-58 | Part #: | 252180 | |
| Descri | ption: SMA Clamp JK | SMA Clamp JK RG58 LMR195 500 | | RG-58 - PE 0.196 | Description: | MCX PLUG RG58 LMR195 500 | |
| Туре: | SMA | | Dielectric: | PE | Туре: | MCX | |
| Gende | er: Jack | | Shielding: | Braid | Gender: | Plug | |
| Body T | Type: Straight | | Diameter: | 0.196 | Body Type: | Straight | |
| Contac | ct Type: Solder | | Impedance: | 50 Ohm | Contact Type: | Crimp | |
| Polarit | ty: Standard | | Sheathing: | None | Polarity: | Standard | |
| Impeda | ance: 50 Ohm | | Testing: | Continuity Hi-Pot | Impedance: | 50 Ohm | |
| Mounti | ing: Cable | | Length: | 0.75 Meter | Mounting: | Cable | |
| Body M | Material: Brass | | | | Body Material: | Brass | |
| Body F | Finish: Gold | | | | Body Finish: | Gold | |
| IP Ratio | ing: None | | | | IP Rating: | None | |
| Contac | ct Material: Beryllium Coppe | r | | | Contact Material: | Brass | |
| Contac | ct Finish: Gold | | | | Contact Finish: | Gold | |
| Max. F | req.: 12.4 GHz | | | | Max. Freq.: | 6 GHz | |
| Bootin | ig: SMA Jack Straig | ht | | | Booting: | MCX Plug Straight | |
| | | | | | Clocking: | 0° | |
| | | AND MUST NOT BE U TAL TO CUSTOM CAI CED OR TRANSCRIBI | BLE ED | Title: SMA-ST-JK/MCX-ST-PL RG58 0.75M | | UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: | |
| | | IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING. | | NG Part No: | | | CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES |



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/2/2023

Part Number: Q-2Z01E0008.75M

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK/MCX-ST-PL RG58 0.75M

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank