



			1		
	Part Number:		DRAWN	8/10/2017	
	MOOO	4204-1	CJ	0/10/2017	
	141009		CHECKED	8/14/2017	
			P.D.	0,11,2017	
	Description:	enser Microphone	APPROVED	8/14/2017	
	Electret Conde		C.E.		

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View




Side View



Bottom View





Additional considerations can be found at www.dbunlimitedco.com/technical-articles.

	Items	Specifications	Conditions					
	Directivity	Omnidirectional						
	Sensitivity	-42 ± 2	dB					
	Frequency Range	50 ~ 16,000	Hz		REVISION HISTORY			
	Rated Voltage	4.5	V	REV	DESCRIPTION	DATE	APPROVED	
	Voltage Range	1 ~ 10	V		Released from Engineering	10/21/2013	J.S.	
	Output Impedance	2,200	Ω	1	Add Pin Dimensions, update to new template, voltage range changed	8/14/2017	C.E.	
^	Max. Rated Current	0.5	mA		NOTES (
	Storage Temperature	-25 ~ +70	°C		All dimensions are in mm unless otherwise noted			
	Operating Temperature	-20 ~ +60	°C		2) All tolerances are ± 0.5 mm unless otherwise noted			
	Signal to Noise Ratio	60	dB		3) All parts meet RoHS			
	Mount Type	Thru Hole			4) Subject to change or redrawn without notice			
	Connection Method	PC Pins						