

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		QT	AT
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +105°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60°C (NOTE3)			
	OPERATING HUMIDITY RANGE	20% TO 80% (NOTE2)	STORAGE HUMIDITY RANGE	40% TO 70% (NOTE3)			
	APPLICABLE CONNECTOR	DF62#-7S-2.2C(##)	VOLTAGE	AC/DC 250V			
APPLICABLE CONTACT	DF62-EP22PC* DF62-EP2428PC* DF62-EP30PC*	CURRENT	AWG 22 : 3A AWG 24 : 2A AWG 26-30 : 1A				
SPECIFICATIONS							
ITEM	TEST METHOD		REQUIREMENTS				
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.			
GENERAL EXAMINATION	CONFIRMED VISUALLY.						
ELECTRIC CHARACTERISTICS							
INSULATION RESISTANCE	500 V.DC.	1000 MΩ MIN.					
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.					
MECHANICAL CHARACTERISTICS							
MECHANICAL OPERATION	30 TIMES INSERTION AND EXTRACTION.		NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.		NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES EACH FOR 3 BOTH AXIAL DIRECTIONS.		NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2°C , 90 TO 95 % , 96 h (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)		①INSULATION RESISTANCE: 1000 MΩ MIN. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55°C → +85°C TIME 30min → 30min UNDER 5 CYCLES. (THE TRANSFERRING TIME OF THE TANK IS 2~3 min) (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)		①INSULATION RESISTANCE: 1000 MΩ MIN. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
<p>NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT.</p> <p>NOTE2: NO CONDENSING</p> <p>NOTE3: APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFOR PCB ON BOARD, AFTER PCB ON BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STRAGE DURING TRANSPORTATION.</p>							
△	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE		
REMARKS		<p>Unless otherwise specified, refer to IEC 60512.</p> <p>Note QT:Qualification Test AT:Assurance Test X:Applicable Test</p>					
DRAWING NO.		ELC4-349140-01					
APPROVED		KI. AKIYAMA		14.03.10			
CHECKED		HK. UMEHARA		14.03.10			
DESIGNED		TS. KUMAZAWA		14.03.07			
DRAWN		TS. KUMAZAWA		14.03.07			
SPECIFICATION SHEET		PART NO.		DF62P-7EP-2. 2C (10)			
HIROSE ELECTRIC CO., LTD.		CODE NO.		CL544-0548-5-10		△ 1/1	