



Quality Products. Service Excellence.

Type 4X Stainless Steel Two Door Floormount Enclosure 1422 N4 SS

Series

Continuous Hinge Door with Clamps



Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.

Standards

- UL 508A Type 3R, 4, 4X, and 12
- CSA Type 3R, 4, 4X, and 12
- Complies with
 - NEMA Type 3R, 4, 4X, 12 and 13
 - IEC 60529, IP66

Construction

- Formed 12 gauge 304 or 316 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Body stiffeners are provided in the larger enclosures for extra rigidity.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Center post is removable for easy installation of the inner panel.
- Formed lip on door and top of enclosure opening exclude flowing liquids and contaminants.
- Continuously hinged doors may be removed by pulling the stainless steel hinge pin.
- Doors are secured with heavy duty stainless steel clamps.
- Provision for padlocking.
- 12" floor stands are welded to the enclosure.
- Seamless poured-in place gasket.
- Panel supports are provided for easy panel installation.
- Collar studs are provided for mounting inner panels.
- A bonding stud is provided on the door and a grounding stud is provided in the enclosure for each door.
- A literature pocket is provided.

Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Removable 10 gauge inner panel is finished in white powder coating.

Accessories

- Additional Inner Panels
- Barrier Kits for Type 4 Floormount
- Door Clamping Hardware
- Window Kits
- Lighting
- Door Stop Kit
- Drip Shield Kit
- Wallmount Quick Release Clamp
- Climate Control
- General Accessories

**New and improved PDF part
drawing files with more detail
now available.**

Click part number in table below
to access PDF, DXF, and STEP files.

| 304 S.S. Part No. | 316 S.S. Part No. | Enclosure | | | Panel | |
|----------------------|----------------------|-----------|-------|-------|-------|-------|
| | | H | W | D | H | W |
| 1422N4SSB12F | 1422N4S16B12F | 60.13 | 48.06 | 12.69 | 56.00 | 44.00 |
| 1422N4SSD12F | 1422N4S16D12F | 60.13 | 60.06 | 12.69 | 56.00 | 56.00 |
| 1422N4SSE12F | 1422N4S16E12F | 72.13 | 60.06 | 12.69 | 68.00 | 56.00 |
| 1422N4SSF12F | 1422N4S16F12F | 72.13 | 72.06 | 12.69 | 68.00 | 68.00 |
| 1422N4SSF24F | 1422N4S16F24F | 72.13 | 72.06 | 24.69 | 68.00 | 68.00 |

Tags: **1422, floormount, two door, stainless steel, Type 4X, NEMA 4X, instrument, hydraulic, pneumatic, 304, 316, continuous hinge, clamps**

Data subject to change without notice

© 2023. Hammond Manufacturing Ltd. All rights reserved.