


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.

ITEM	CONNECTOR PART NO.	DESCRIPTION
1	SSH-003T-P0.2-H	SH CONNECTOR CONTACT
2	UL1571, 28 AWG	BLACK - BCD

Applicable Housings			
SH SERIES			APSH SERIES
NO. OF CIRCUITS	HOUSING PART NO. WITH PROTRUSIONS	HOUSING PART NO. WITHOUT PROTRUSIONS	HOUSING PART NO.
2	SHR-02V-S-B	SHR-02V-S	
3	SHR-03V-S-B	SHR-03V-S	APSHR-03V-S
4	SHR-04V-S-B	SHR-04V-S	
5	SHR-05V-S-B	SHR-05V-S	
6	SHR-06V-S-B	SHR-06V-S	
7	SHR-07V-S-B	SHR-07V-S	
8	SHR-08V-S-B	SHR-08V-S	
9	SHR-09V-S-B	SHR-09V-S	
10	SHR-10V-S-B	SHR-10V-S	
11	SHR-11V-S-B	SHR-11V-S	
12	SHR-12V-S-B	SHR-12V-S	
13	SHR-13V-S-B	SHR-13V-S	
14	SHR-14V-S-B	SHR-14V-S	
15	SHR-15V-S-B	SHR-15V-S	
20	SHR-20V-S-B	-	



Electrical Specifications
Current: 1.0A AC/DC
Voltage: 50V AC/DC



SCALE	1:1
DIMENSIONS	All dimensions are in MM with a tolerance of +/- 3.0 unless otherwise specified.
DRAWN BY	STEVEN PILKINGTON
CHECKED BY	JUSTIN BAKER

DESCRIPTION	1.0 mm Pitch SH & APSH Series Standard Leads - 2" Inside Length DOUBLE-END LEADS	
ASSEMBLY PART NO.	ASSHSSH28K51	
DRAWING NO. & REVISION	GAM-049	DATE
		3/8/2016

REV.	DESCRIPTION	DATE	BY
3	Add electrical specifications	7/2/2018	SP
2	Revised wire to BCD (Hitachi) type for better processing	8/4/2017	SP
1	Added applicable housings for the APSH series	4/6/2017	SP

4

3

2

1

D

C

B

A

D

C

B

A