



SIGN	DATE	DESCRIPTION	APPROVER
△	4/01'09	Current, wire range, torque, safety approval are changed	Jody
△	11/17'09	Wire guard solder pin is changed from Brass to Copper	Aaron

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
- Item 2 Clamp : Steel stamping , Zinc plated
- △ ● Item 3 Wire guard solder pin : Copper, Tin plated
- Item 4 Terminal screw: Steel Zinc plating"- "slot type

Electrical cULs IEC

- Voltage rating : 300V 1000V
- △ ● Current rating : 65A 76A
- Wire range : 16.00mm²
- Solid wire (AWG) : 6-20
- Stranded wire (AWG) : 6-20
- △ ● Torque (LB-In.) : 19Lb-In / 1.2N.m
- Screw : M4.5
- Wire strip length : 10-11mm
- △ ● Withstanding voltage : 1.6KV 6KV
- Operating temperature : -40°C+115°C
- Soldering temperature : 250°C+10°C/5 Sec
- △ ● Safety Approval : cULus

VP xx 85 x 5 xxxx G

02 2 CONTACTS	0: Black	0000 Standard @ Logo	RoHS
03 3 CONTACTS	5: Green (RAL 6018/T)	000A Standard ANY Logo	Pb<40,000ppm
... ..	6: Blue	Any special item by customer request,	
12 12 CONTACTS	8: Grey (RAL 7035/D)	please contact sales department.	

Poles	02	03	04	05	06	07	08	09	10	11	12	
Dim L	25.40	38.10	50.80	63.50	76.20	88.90	101.60	114.30	127.0	139.70	152.40	
Dim B	17.78	30.48	43.18	55.88	68.58	81.28	93.98	106.68	119.38	132.08	144.78	
TOL	±0.20				±0.30				±0.40			

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		VP 12.70 Series (Double tail) Contacts Pin Pitch 5.08mm					
PART NO.		VPxx85x5xxxxG			DWG NO.		8VP0101
APPROVED		CHECKED		DESIGNED		DRAWN	
		Aaron 2009.11.17		Aaron 2009.11.17		CUST NO.	
						Tolerance	
						X. ±0.50	
						X.X ±0.30	
						X.XX ±0.10	
						X° ±1°	
				SHEET: 01/01		REV.: D	