

CTCDRH125F Series

From 1.3µH to 1,000µH

ENGINEERING KIT #23F



SPECIFICATIONS

Part numbers indicate inductance tolerance available.

M = ±20%, N = ±30%

*IDC: The DC current at which the inductance decreases to 75% of its nominal value or when ΔT=40°C, whichever is lower (Ta=20°C).

Part Number	Inductance (µH)	L Test Freq. (KHz)	DCR Max. (Ω)	IDC Max. (A)
CTCDRH125F-1R3N	1.3	1.0	.012	8.0
CTCDRH125F-2R1N	2.1	1.0	.014	7.0
CTCDRH125F-3R1N	3.1	1.0	.017	6.0
CTCDRH125F-4R4N	4.4	1.0	.020	5.0
CTCDRH125F-5R8N	5.8	1.0	.021	4.4
CTCDRH125F-7R5N	7.5	1.0	.024	4.2
CTCDRH125F-7R6N	7.6	1.0	.026	4.5
CTCDRH125F-100M	10	1.0	.03	4.0
CTCDRH125F-120M	12	1.0	.03	3.5
CTCDRH125F-150M	15	1.0	.03	3.3
CTCDRH125F-180M	18	1.0	.03	3.0
CTCDRH125F-220M	22	1.0	.04	2.8
CTCDRH125F-270M	27	1.0	.05	2.3
CTCDRH125F-330M	33	1.0	.06	2.1
CTCDRH125F-390M	39	1.0	.07	2.0
CTCDRH125F-470M	47	1.0	.08	1.8
CTCDRH125F-560M	56	1.0	.11	1.7
CTCDRH125F-680M	68	1.0	.12	1.5
CTCDRH125F-820M	82	1.0	.14	1.4
CTCDRH125F-101M	100	1.0	.16	1.3
CTCDRH125F-121M	120	1.0	.17	1.1
CTCDRH125F-151M	150	1.0	.23	1.0
CTCDRH125F-181M	180	1.0	.29	0.9
CTCDRH125F-221M	220	1.0	.40	0.8
CTCDRH125F-271M	270	1.0	.46	0.8
CTCDRH125F-331M	330	1.0	.51	0.7
CTCDRH125F-391M	390	1.0	.69	0.7
CTCDRH125F-471M	470	1.0	.77	0.6
CTCDRH125F-561M	560	1.0	.86	0.5
CTCDRH125F-681M	680	1.0	1.2	0.5
CTCDRH125F-821M	820	1.0	1.3	0.4
CTCDRH125F-102M	1000	1.0	1.5	0.4

CHARACTERISTICS

Description: SMD (shielded) power inductor

Applications: Power supplies for OA equipment, LCD televisions, PC notebooks, portable communication equipment, DC/DC converters, etc.

Operating Temperature: -40°C to +125°C

Storage Condition: Temperature range = 15°C ~ 28°C;

Humidity = <80% relative humidity

Inductance Tolerance: ±20%, ±30%

Testing: Inductance is tested on an HP4284A at 1.0kHz

Packaging: Tape & Reel

Marking: Parts are marked with inductance code

Miscellaneous: RoHS Compliant.

Additional Information: Additional electrical & physical information available upon request

Samples available. See website for ordering information.

PHYSICAL DIMENSIONS

Size	A	B	C	D
	Max.	Max.		
mm	12.8	6	7.6±0.2	5±0.2
inches	0.504	0.24	0.30±0.008	0.2±0.007

