



MODULAR JACKS AND PLUGS: GDLX Series
Right Angle Modular Jack

Product Features

Available in high temp for Reflow compatibility
Panel Stops, Shielding and Keying Options Available
Snap-In Board Retention Tabs
CSA/NRTL Certified File No. LR78160

Performance Specifications

Materials and Finish

Housing Material

PBT Thermoplastic, Glass Filled, UL 94V-0 Rated,
Black Color

Shield Material

Copper Alloy, Nickel Plated

Contact Material

Phosphor Bronze

Electrical Characteristics

Insulation Resistance

500 Megohms Min.

Dielectric Withstanding Voltage

1000V AC for 1 Minute

Contact Resistance

20 milliohms Max.

Current Rating

1.5A

Voltage Rating

125V DC

Generated Part Number

GDLX-A-64

Part Number Builder

GDLX	-	A	64	
Series		Shield Option	Positions & Contacts	Plating Option

Series

GDLX - Right Angle Modular Jack PCB Mount

Shield Options

- A - With Panel Stops, Non-Shielded
- N - Without Panel Stops, Non-Shielded
- S - With Panel Stops, Shielded

Number of Positions / Contacts

- 6 Positions / 4 Contacts
- 6 Positions / 6 Contacts
- 8 Positions / 8 Contacts

Plating Option

- Gold Flash
- 50µ" Gold Plating

Contact Kycon for Keyed and other Options

GDLX Series

Dimensions in mm

GDLX-A-64

