## 84 INCHES LENGTH



Connector A 132114 SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 122428 TNC Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

|                | Connector A                              |                  |   | Cable   |                           |                                    | Connector B                              |   |  |
|----------------|--|------------------|---|---|---------------------------|------------------------------------|--|---|--|
|                | Part #:                                  | 132114           |   | Part #:   | RG-316                    | Part #:                            | 122428                                   |   |  |
|                | Description:                             | SMA PLUG RG17    | 74 RG316 LMR100 500                                   | Description:<br>Dielectric:   | RG-316 - ST 0.102<br>ST   | Description:                       | TNC BHD JK RG174 RG316 LMR100 500<br>TNC |   |  |
|                | Туре:                                    | SMA              |   |   |                           | Type:                              |  |   |  |
|                | Gender:                                  | Plug             |   | Shielding:  | Braid                     | Gender:                            | Jack                                     |   |  |
|                | Body Type:                               | Straight         |   | Diameter:   | 0.102                     | Body Type:                         | Straight                                 |   |  |
|                | Contact Type:                            | Solder           |   | Impedance:  | 50 Ohm                    | Contact Type:                      | Crimp                                    |   |  |
|                | Polarity:                                | Standard         |   | Sheathing:<br>Testing:  | None<br>Continuity Hi-Pot | Polarity:<br>Impedance:            | Standard<br>50 Ohm                       |   |  |
|                | Impedance:                               | 50 Ohm           |   |   |                           |                                    |  |   |  |
|                | Mounting:                                | Cable            |   | Length:   | 84 Inches                 | Mounting:                          | Bulkhead - Rear Mo                       | unt                                     |  |
|                | Body Material:                           | Brass            |   |   |                           | Body Material:                     | Brass                                    |   |  |
|                | Body Finish:                             | Gold             |   |   |                           | Body Finish:                       | Nickel                                   |   |  |
|                | IP Rating:                               | None             |   |   |                           | IP Rating:                         | None                                     |   |  |
|                | Contact Material:                        | Brass            |   |   |                           | Contact Material:                  | Phosphor Bronze                          |   |  |
|                | Contact Finish:                          | Gold             |   |   |                           | Contact Finish:                    | Gold                                     |   |  |
|                | Max. Freq.:                              | 12.4 GHz         | nt  |   |                           | Max. Freq.:                        | 11 GHz<br>TNC Jack Straight BHD          |   |  |
|                | Booting:                                 | SMA Plug Straigh |   |   |                           | Booting:                           |  |   |  |
|                |  |                  |   |   |                           | Clocking:                          | 0°                                       |   |  |
| mphonol        | mphenol                                  |                  |   |   | Title:<br>SMA-ST-PL/TNC-S | T- IK C316 84I                     |  | UNLESS SPECIFIED<br>TOLERANCE:          |  |
|                |  |                  | FOR ANY PURPOSE DETRIME!<br>INC. IT MAY NOT BE REPROD | NTAL TO CUSTOM CA<br>UCED OR TRANSCRIB  | BLE<br>ED                 | 5MA-51-1 L/ MC-51-JK (510 041      |  | 0-18 inches +/- 1/2"<br>over 18" +/- 2% |  |
| JUSI UNI CABLE |  |                  |   | IN ANY FORM WITHOUT THE WRITTEN CONSENT OF<br>CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING<br>ESTABLISHES AND AGREEMENT OF THE FOREGOING. |                           | Part No:                           |  | ASSEMBLY:<br>CENTER LABEL IF LENG       |  |
| CONTROLLED DOC | <b>CONTROLLED DOCUMENT - DO NOT COPY</b> |                  |   |   |                           | Part No:<br><b>O-3B04F0005084I</b> |  | IS LESS THAN 12 INCHES                  |  |



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/1/2023

Part Number: Q-3B04F0005084I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-PL/TNC-ST-JK G316 84I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank