

AMP | Timer Connector System

TE Internal #: 1-965423-1 Housing for Male Terminals, Wire-to-Panel, 10 Position, .197 in [5 mm] Centerline, Black, Wire & Cable, Signal, Panel Mount, Timer Connector System

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Timer Connector Housing



Connector & Housing Type: Housing for Male Terminals

Connector System: Wire-to-Panel

Number of Positions: **10**

Centerline (Pitch): 5 mm [.197 in]

Sealable: No

All Timer Connector Housing (589)

Features

Product Type Features

Connector Shape

Connector & Housing Type

Rectangular

Housing for Male Terminals

Connector System	Wire-to-Panel
Sealable	No
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	10
Number of Rows	2
Electrical Characteristics	
Nominal Voltage Architecture	12 V
Body Features	
Primary Product Color	Black
Connector & Keying Code	A1
Contact Features	

C For support call+1 800 522 6752

07/31/2023 04:20AM | Page 1

Housing for Male Terminals, Wire-to-Panel, 10 Position, .197 in [5 mm] Centerline, Black, Wire & Cable, Signal, Panel Mount, Timer Connector System



Contact Size	2.8mm
Contact Type	Tab
Contact Current Rating (Max)	11 A
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Panel Mount
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	5 mm[.197 in]
Dimensions	
Connector Height	38 mm[1.496 in]
Product Width	26.6 mm[1.047 in]
Product Length	29.3 mm[1.154 in]
Row-to-Row Spacing	6 mm[.236 in]

Usage Conditions

Operating Temperature (Max)	80 °C[176 °F]
Operating Temperature Range	-40 – 80 °C[-40 – 176 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Method	Box
Other	
Serviceable	No
Connector Position Assurance Capable	No
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant

Housing for Male Terminals, Wire-to-Panel, 10 Position, .197 in [5 mm] Centerline, Black, Wire & Cable, Signal, Panel Mount, Timer Connector System



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Also in the Series | Timer Connector System

Housing for Male Terminals, Wire-to-Panel, 10 Position, .197 in [5 mm] Centerline, Black, Wire & Cable, Signal, Panel Mount, Timer Connector System










PCB Headers & Receptacles(82)

Quick Disconnects(4)

Customers Also Bought



Documents

Product Drawings TAB HOUSING2,8 10POS		
English		
CAD Files 3D PDF		
English		
Customer View Model		

Housing for Male Terminals, Wire-to-Panel, 10 Position, .197 in [5 mm] Centerline, Black, Wire & Cable, Signal, Panel Mount, Timer Connector System



ENG_CVM_1-965423-1_B1.2d_dxf.zip

English

Customer View Model

ENG_CVM_1-965423-1_B1.3d_igs.zip

English

Customer View Model

ENG_CVM_1-965423-1_B1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Timer Interconnection System

English

Instruction Sheets CONNECTEURS JPT ETANCHES A ETRIER POUR CONNEXIONS FIL A FIL PRECONISAT English

Instruction Sheet (non U.S.)

English