



Product: <u>5202FE</u> ☑

Security & Sound, #16-4c, BC, Shielded, CMR

Product Description

Security & Sound Cable, Riser-CMR, 4-16 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Product Overview

Product O	verview								
Suitable Applications: Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment									
Construct	ion Details								
Conductor									
Element	No. of Element	s Size	Stranding	Material					
Conductor(s)			19x29	BC - Bare Copper					
Insulation									
Element	Material	Nom. Thic	kness No	m. Insulation Diame	ter Color Code				
Conductor(s)	PO - Polyolefin	0.008 in (0.2	20 mm) 0.0	73 in (1.9 mm)	Black, Red, White, Green				
Outer Shield									
Shield Type Material Coverage Drainwire Type									
Таре	Bi-Laminate (Alu	um+Poly) 10	00% 24	AWG (7x32) TC					
Outer Jacket									
Mate	rial Non	n. Thickness	s Nom. D	ameter Ripcord					
PVC - Polyvir	nyl Chloride 0.01	7 in (0.43 mn	n) 0.214 in	(5.44 mm) Yes					
Overall Cable	e Diameter (Nomin	nal): 0.214 in	n (5.44 mm)		α.				
Electrical Characteristics									
Electricals									
Element	Nom. Conducto	or DCR Nor	m. Capacita	nce Cond-to-Cond	Nom. Capacitance Cond-to-O	Other (Conds + Shield)	Max. Current		
Conductor(s)	4 Ohm/1000ft	30.	5 pF/ft (100 p	pF/m)	55 pF/ft (180 pF/m)		5.0 Amps per conductor @ 25°C		
Voltage									
UL Voltage F	Rating								
300 V (CMR)									
Mechanical Characteristics									
Tomoroutumo									
Temperature	ture Operating	a							
75°C	-20°C to +7								
Bend Radius									
Stationary M									
2.1 in (53 mm		-							
Max. Pull Ter	nsion:	146 lbs	(66.2 kg)						

Bulk Cable Weight:

44 lbs/1000ft

Standards and Compliance

Environmental Suitability:Indoor - Riser, IndoorFlammability / Reaction to Fire:UL 1666 Riser, FT4, IEC 60332-1-2CPR Compliance:CPR Euroclass: EcaNEC / UL Compliance:Article 800, CMRCEC / C(UL) Compliance:CMGEuropean Directive Compliance:UL CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEEEUK Regulation Compliance:UKCA MarkAPAC Compliance:China RoHS II (GB/T 26572-2011)Plenum Number:6202FE	-					
CPR Compliance:CPR Euroclass: EcaNEC / UL Compliance:Article 800, CMRCEC / C(UL) Compliance:CMGEuropean Directive Compliance:EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEEUK Regulation Compliance:UKCA MarkAPAC Compliance:China RoHS II (GB/T 26572-2011)	Environmental Suitability:	Indoor - Riser, Indoor				
NEC / UL Compliance: Article 800, CMR CEC / C(UL) Compliance: CMG European Directive Compliance: EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEEE UK Regulation Compliance: UKCA Mark APAC Compliance: China RoHS II (GB/T 26572-2011)	Flammability / Reaction to Fire:	UL 1666 Riser, FT4, IEC 60332-1-2				
CEC / C(UL) Compliance: CMG European Directive Compliance: EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE UK Regulation Compliance: UKCA Mark APAC Compliance: China RoHS II (GB/T 26572-2011)	CPR Compliance:	CPR Euroclass: Eca				
European Directive Compliance: EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE UK Regulation Compliance: UKCA Mark APAC Compliance: China RoHS II (GB/T 26572-2011)	NEC / UL Compliance:	Article 800, CMR				
UK Regulation Compliance: UKCA Mark APAC Compliance: China RoHS II (GB/T 26572-2011)	CEC / C(UL) Compliance:	CMG				
APAC Compliance: China RoHS II (GB/T 26572-2011)	European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)				
	UK Regulation Compliance:	UKCA Mark				
Plenum Number: 6202FE	APAC Compliance:	China RoHS II (GB/T 26572-2011)				
	Plenum Number:	6202FE				

History

Update and Revision: Revision Number: 0.477 Revision Date: 04-03-2023

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC/EAN	Footnote
5202FE.00152	Chrome	Reel	152 m	8719605008077	
5202FE.00305	Chrome	Reel	305 m	8719605008084	
5202FE 0081000	Gray			612825157854	С
5202FE 008500	Gray			612825157861	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.