

## FGD2N40L 400V N-Channel Logic Level IGBT

### Features



- $V_{CE(SAT)} = 1.6V @ I_C = 2.5A, V_{GE} = 2.4V$
- 6kV ESD Protected
- High Peak Current Density
- TO-252 (D-Pak)
- Low  $V_{GE(TH)}$

### Applications

- Small Engine Ignition Applications

### General Description

This N-Channel IGBT is a MOS gated, logic level device which has been especially tailored for small engine ignition applications. The gate is ESD protected with a zener diode.



**Device Maximum Ratings**  $T_A = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Ratings	Units
$BV_{CES}$	Collector to Emitter Breakdown Voltage	400	V
$I_C$	Collector Current Continuous(DC)	7	A
$I_{CP}$	Collector Current Pulsed(100 $\mu\text{s}$ )	29	A
$V_{GES}$	Gate to Emitter Voltage Continuous(DC)	$\pm 8$	V
$V_{GEP}$	Gate to Emitter Voltage Pulsed	$\pm 10$	V
$P_D$	Power Dissipation Total $T_C = 25^\circ\text{C}$	29	W
$T_J$	Operating Junction Temperature Range	-40 to 150	$^\circ\text{C}$
$T_{STG}$	Storage Junction Temperature Range	-40 to 150	$^\circ\text{C}$
ESD	Electrostatic Discharge Voltage at 100pF, 1500 $\Omega$	6	kV

**Package Marking and Ordering Information**

Device Marking	Device	Package	Tape Width	Quantity
FGD2N40	FGD2N40L	D-PAK	12mm / 16mm	2500

**Electrical Characteristics**  $T_A = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

**Off Characteristics**

$BV_{CES}$	Collector to Emitter Breakdown Voltage	$I_C = 1\text{mA}$ , $V_{GE} = 0\text{V}$	400	-	-	V	
$BV_{GES}$	Gate-Emitter Breakdown Voltage	$I_{GES} = \pm 1\text{mA}$	$\pm 10$	-	-	V	
$I_{CES}$	Collector to Emitter leakage Current	$V_{CE} = 320\text{V}$	$T_C = +25^\circ\text{C}$	-	-	10	$\mu\text{A}$
			$T_C = +125^\circ\text{C}$	-	-	250	$\mu\text{A}$
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE} = \pm 8$	-	-	$\pm 10$	$\mu\text{A}$	

**On Characteristics**

$V_{CE(SAT)}$	Collector to Emitter Saturation Voltage	$I_C = 2.5\text{A}$ , $V_{GE} = 2.4\text{V}(\text{NOTE1})$	-	1.3	1.6	V
---------------	---	--	---	-----	-----	---

**Dynamic Characteristics**

$Q_{G(ON)}$	Gate Charge	$I_C = 2.5\text{A}$ , $V_{CE} = 300\text{V}$ , $V_{GE} = 10\text{V}$	-	11	-	nC
$V_{GEP}$	Gate to Emitter Plateau Voltage	$I_C = 2.5\text{A}$ , $V_{CE} = 300\text{V}$	-	1.8	-	V
$V_{GE(TH)}$	Gate to Emitter Threshold Voltage	$I_C = 1.0\text{mA}$ , $V_{CE} = V_{GE}$	0.70	0.85	1.2	V
$C_{IES}$	Input Capacitance	$V_{CE} = 10\text{V}$ , $V_{GE} = 0\text{V}$ , $f = 1\text{MHz}$	-	357	-	pF
$R_G$	Internal Gate Series Resistance			300		ohms

**Switching Characteristics**


$t_{ON}$	Turn-On Time	$V_{CC} = 300\text{V}$ , $I_C = 2.5\text{A}$ , $V_{GE} = 4\text{V}$ , $R_L = 120\Omega$ , $R_G = 51\Omega$ , $T_J = 25^\circ\text{C}$	-	0.142	-	$\mu\text{s}$
$t_{d(ON)I}$	Current Turn-On Delay Time		-	0.047	-	$\mu\text{s}$
$t_{rI}$	Current Rise Time		-	0.095	-	$\mu\text{s}$
$t_{OFF}$	Turn-Off Time		-	2.152	-	$\mu\text{s}$
$t_{d(OFF)I}$	Current Turn-Off Delay Time		-	0.650	-	$\mu\text{s}$
$t_{fI}$	Current Fall Time		-	1.529	-	$\mu\text{s}$

**Thermal Characteristics**


$R_{\theta JC}$	Thermal Resistance Junction-Case	TO-252 (D-Pak)	-	-	4.29	$^\circ\text{C/W}$
-----------------	----------------------------------	----------------	---	---	------	--------------------

**Notes:**1: Pulse Duration = 100  $\mu\text{sec}$


## Typical Performance Characteristics




**Figure 1. Collector Current Vs. Collector to Emitter On-State Voltage**




**Figure 2. Collector Current Vs. Collector to Emitter On-State Voltage**




**Figure 3. Collector Current Vs. Collector to Emitter On-State Voltage**



**Figure 4. Collector Current Vs. Collector to Emitter On-State Voltage**




**Figure 5. Collector to Emitter Saturation Voltage Vs. Junction Temperature**




**Figure 6. Collector to Emitter Saturation Voltage Vs. Junction Temperature**


## Typical Performance Characteristics




**Figure 7. Collector to Emitter On-State Voltage Vs. Gate to Emitter Voltage**




**Figure 8. Collector to Emitter On-State Voltage Vs. Gate to Emitter Voltage**




**Figure 9. Collector to Emitter On-State Voltage Vs. Gate to Emitter Voltage**



**Figure 10. Collector to Emitter On-State Voltage Vs. Gate to Emitter Voltage**



**Figure 11. Normalized Gate to Emitter Threshold Voltage Vs. Junction Temperature**



**Figure 12. Capacitance Vs. Collector to Emitter Voltage**

### Typical Performance Characteristics




Figure 13. Switching Time Vs. Collector Current




Figure 14. Switching Time Vs. Gate Resistance




Figure 15. Gate Charge




Figure 16. Transfer




Figure 17. Normalized Collector to Emitter Breakdown Voltage Vs. Junction Temperature

**TRADEMARKS**

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE <sub>x</sub> <sup>™</sup>	FAST <sup>®</sup>	ISOPLANAR <sup>™</sup>	PowerSaver <sup>™</sup>	SuperSOT <sup>™</sup> -6
ActiveArray <sup>™</sup>	FAST <sub>r</sub> <sup>™</sup>	LittleFET <sup>™</sup>	PowerTrench <sup>®</sup>	SuperSOT <sup>™</sup> -8
Bottomless <sup>™</sup>	FPS <sup>™</sup>	MICROCOUPLER <sup>™</sup>	QFET <sup>®</sup>	SyncFET <sup>™</sup>
Build it Now <sup>™</sup>	FRFET <sup>™</sup>	MicroFET <sup>™</sup>	QST <sup>™</sup>	TCM <sup>™</sup>
CoolFET <sup>™</sup>	GlobalOptoisolator <sup>™</sup>	MicroPak <sup>™</sup>	QT Optoelectronics <sup>™</sup>	TinyLogic <sup>®</sup>
CROSSVOLT <sup>™</sup>	GTO <sup>™</sup>	MICROWIRE <sup>™</sup>	Quiet Series <sup>™</sup>	TINYOPTO <sup>™</sup>
DO <sub>M</sub> E <sup>™</sup>	HiSeC <sup>™</sup>	MSX <sup>™</sup>	RapidConfigure <sup>™</sup>	TruTranslation <sup>™</sup>
EcoSPARK <sup>™</sup>	I <sup>2</sup> C <sup>™</sup>	MSXPro <sup>™</sup>	RapidConnect <sup>™</sup>	UHC <sup>™</sup>
E <sup>2</sup> CMOS <sup>™</sup>	<i>i-Lo</i> <sup>™</sup>	OCX <sup>™</sup>	μSerDes <sup>™</sup>	UltraFET <sup>®</sup>
EnSigna <sup>™</sup>	ImpliedDisconnect <sup>™</sup>	OCXPro <sup>™</sup>	ScalarPump <sup>™</sup>	UniFET <sup>™</sup>
FACT <sup>™</sup>	IntelliMAX <sup>™</sup>	OPTOLOGIC <sup>®</sup>	SILENT	VCX <sup>™</sup>
FACT Quiet Series <sup>™</sup>		OPTOPLANAR <sup>™</sup>	SWITCHER <sup>®</sup>	Wire <sup>™</sup>
		PACMAN <sup>™</sup>	SMART START <sup>™</sup>	
		POP <sup>™</sup>	SPM <sup>™</sup>	
Across the board. Around the world. <sup>™</sup>		Power247 <sup>™</sup>	Stealth <sup>™</sup>	
The Power Franchise <sup>®</sup>		PowerEdge <sup>™</sup>	SuperFET <sup>™</sup>	
Programmable Active Droop <sup>™</sup>			SuperSOT <sup>™</sup> -3	

**DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**PRODUCT STATUS DEFINITIONS**

**Definition of Terms**

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Rev. I18