0.75 METER LENGTH



Connector A 132117 SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122454 TNC Jack Right Angle Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A				Cable		Connector B		
6 7 6 6 7 8 9 8 9 9 9 9 9 1 1 1 1 1 1 1 1 1 1 1 1	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: P Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132117 SMA JK RG174 R SMA Jack Straight Solder Standard 50 Ohm Cable Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Straigh	G316 LMR100 50O	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 0.75 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	122454 TNC R/A BHD JK F 500 TNC Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mo Brass Nickel None Phosphor Bronze Gold 11 GHz TNC Jack Right Ang 0°		
Amphenol CUSTOM CABLE			PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIME INC. IT MAY NOT BE REPROD IN ANY FORM WITHOUT THE CUSTOM CABLE INC. ACCEPT	IIS DRAWING MAY CONTAIN PATENTED OR OPRIETARY INFORMATION AND MUST NOT BE USED OR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE C. IT MAY NOT BE REPRODUCED OR TRANSCRIBED ANY FORM WITHOUT THE WRITTEN CONSENT OF JSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING TABLISHES AND AGREEMENT OF THE FOREGOING.				UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	