

6

5

4

3

2

1

E

E

D

D

C

C

B

B

A

A

6

5

4

3

2

1

STAINLESS STEEL SCREWS W/LOCK WASHER (6) REQ'D

F3 MAX-LOC NUT FOR MESH

STAINLESS STEEL SCREWS W/FLAT WASHER 1 $\frac{1}{2}$ AND O'RING

STAINLESS STEEL SUPPORT RINGS (2) REQ'D

9.77"

SINGLE SPEED MOMENTARY NO/NC (505SW-1N0NC)

3-POSITION SELECTOR SWITCH NO IN CENTER (505SS-3NO)

MAINTAINED E-STOP SWITCH (505B-RM)

1.18" BETWEEN CENTERS

3.52"

2.31"

NOTES:

- 1. INSTALLATION INSTRUCTIONS, BUTTON ID. LABELS ARE PACK WITH THE PART.
- 2. ALL BUTTONS ARE HIGH AMBIENT, CHEMICALLY RESISTANT MATERIAL - COLOR BLACK

RELEASE CUSTOMER DWG EC NO: IPC2015-0777 DRWN: HRUIZ01 2014/10/24 CHKD: HKNEELAN 2014/10/24 APPR: JFMURPHY 2015/04/22	QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
			mm	INCH	DRAWN BY HRUIZ01	DATE 2014/10/24	TITLE 4 POS PENDANT W/ 505SW-1N0NC 505SS-3NO; 505B-RM			
		4 PLACES	±---	±---	CHECKED BY HKNEELAN	DATE 2014/10/24	MOLEX INCORPORATED			
		3 PLACES	±---	±.005	APPROVED BY JFMURPHY	DATE 2015/04/22				
2 PLACES	±---	±.010	ANGULAR ±1/2°		MATERIAL NO. 130126-0352	DOCUMENT NO. SD-130126-067	SHEET NO. 1 OF 1			
1 PLACE	±---	±.020	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					