



# NLS-FM100-M

## FIXED MOUNT BARCODE SCANNER

### FEATURES

- **Ease of integration**

Compact and easy to integrate design. The small form factor enables easy integration into various solutions. The NLS-FM100-M has an IP54 rating meaning it is dust -and water resistant.

- **Advanced Technology**

Armed with core technology **UIMG®**, which is independently designed and manufactured by Newland Auto-ID. **UIMG®** technology includes the optical, CMOS, digitizer, decoder, image processing & embedded systems. The scanner supports all global standard ID barcode symbologies. Its reading performance exceeds global standards. By using the accessories provided, the user can ideally set up the scanner to its user environment.



CCD



ID Barcode



RS232



USB

# NLS-FM100-M

## Performance

Image Sensor	2500 Linear imager
Illumination	0 ~ 100,000 LUX
Symbologies	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN / ISSN, Code 93, UCC/EAN-128, GSI Databar, etc.
Precision	≥5mil ( condition: PCS=0.9, testing code: Code 39)
Light Source	LED (622nm - 628nm)
Light Intensity	265 LUX (130mm)
Depth of Scan Field	40mm-430mm
Print Contrast Signal	≥30%
Scan Angle**	Roll: ±30°, Pitch: ±65°, Skew: ±60°

## Physical

Interface	RS-232, USB 1.1
Power Consumption	1.25W
Voltage	DC 5V
Current	Operating 170mA (typical), 250mA (max.) Idle 65mA
Dimensions	37(W)×26(D)×49(H) mm
Weight	68g

## Environmental

Operating Temperature	-5°C to 45°C (23°F to 113°F)
Storage Temperature	-40°C to 60°C (-40°F to 140°F)
Humidity	5% - 95% (non-condensing)

## Certificates

Certificates & Protection	FCC Part 15 Class B, CE EMC Class B, RoHS
---------------------------	---

## Accessories

Cable	USB	Used to connect the NLS-FM100-M to a host device.
	RS-232	Equipped with a power connector; used to connect the NLS-FM100-M to a host device.
Power Adapter		Used to provide power for the NLS-FM100-M. Output: DC 5V, 2A; Input: AC100-240V, 50-60HZ.

\*\*Test conditions:

Code 39: 3 Bytes ; Resolution = 10mil; W:N = 3:1 ; PCS = 0.8 ;

Barcode Height = 11mm; Distance = 120mm; T=23°C; Illumination= 200 LUX

Specifications are subject to change without notice.

Version: V1.3

### Newland AIDC

Add: No.1 Rujiang West Rd.,  
Mawei, Fuzhou, Fujian 350001, China  
Tel: +86-591-83979500  
Fax: +86-591-83979216  
Email: info@nlscan.com  
Web: www.newlandaidc.com

### North America & Latin America

Add: 46559 Fremont Blvd.,  
Fremont, CA 94538, USA  
Tel: +1 510 490 3888  
Fax: +1 510 490 3887  
Email: info@nlscan.com  
Web: www.newlandamerica.com

### Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,  
The Netherlands  
Tel: +31 (0) 345 87 00 33  
Email: sales@newland-id.com  
Tech Support: tech-support@newland-id.com  
Web: www.newland-id.com

### Asia Pacific

Taiwan:  
Add: 7F-6, No. 268, Liancheng Rd.,  
Jhonghe Dist. 235, New Taipei City, Taiwan  
Tel: +886 2 7731 5388  
Email: info@newland-id.com.tw