






Bestückungsplan - contact layout



■ = bestückt - assemble



Lochbild für Leiterplatte (Bestückungsseite) Board hole pattern (Component mounting side)



EE-Zone für durchkontaktierte Löcher $\varnothing 0.6 \pm 0.05$
Compliant zone for thru hole $\varnothing 0.6 \pm 0.05$

- 1) $\varnothing 0.6 \pm 0.05$ Durchmesser des metallisierten Loches
 $\varnothing 0.6 \pm 0.05$ Diameter of finished plated-through hole
 $\varnothing 0.7 \pm 0.02$ Bohrungsdurchmesser des Loches
 $\varnothing 0.7 \pm 0.02$ Diameter of drilled hole

Schichtaufbau im metallisierten Loch
siehe Zeichnung 114406

Metal plating of plated-through hole
see drawing 114406

Fehlende Masse und Angaben nach IEC 61076-4-101
Missing information and dimensions per IEC 61076-4-101

Bedruckung siehe Zeichnung 401194
Marking see drawing 401194

Au - Plating !

Consider protection memo from DIN 34

Information: Anforderungsstufe 207 / class 207				Tolerances  All Dimensions in mm		Scale 2:1	
All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.		Designation ERmet Federleiste DE <i>ERmet Female Type DE</i>	
				 www.ERNI.com		225009	
Index		Date		M:00066988 SZA		ERMDE	

Consider protection memo from DIN 34